

Regional Intergovernmental Council LONG RANGE TRANSPORTATION PLAN AND TRAVEL DEMAND MODEL

Tuesday, October 26, 2010



Base

Kimley-Horn and Associates, Inc.



Allison Fluitt, P.E., AICP

PLANNING PROCESS





Changing Conditions

- 2005 Projection \$842 million (\$32.4 million annually)
- 2008 Projection \$469 million (\$14.7 million annually)
- Shift in mindset needed for future success











2009 Existing Deficiencies




2040 Highway Deficiencies




Planning Process

- Steering Committee
 - RIC, WVDOT, FHWA, and WVDEP
- Public Outreach
 - Workshops in July and October
 - Stakeholder Outreach
 - Online Public Questionnaire
- Conversion to new Model Platform
- Federal Highway Administration Compliant Process







Planning Process

- Range of project types needed
 - Access management
 - Safety and intersection improvements
 - Large capacity projects
 - Multimodal integration














Phased Project Solutions

- Short-term: smaller, cost-effective projects
 - Relieve critical bottlenecks
 - Improve safety and reduce conflict points
 - Enhance intersection capacity
 - Rehabilitate key connections
- Long-term: larger, more costly projects
 - Larger scale improvements
 - Small area and regional congestion relief





Recommended Highway Plan



Tools for Implementation

- Best Practices Toolbox
 - Access management
 - Complete streets
 - ITS
- Visualization of improvements
- Model application
- Clear prioritization process







Access Management

- Protecting key corridors
- Safety & Mobility
- Small, cost-effective projects





Teays Valley Road today (near Lake Chadesa Drive) Teays Valley Road after implementation of median and left-over treatments





Evaluation Matrix

| | Table 4.2 - Roadway Project Total Benefit and Impact Matrix | | | | | | | | | | | | | | | | | | | |
|-------------|---|---|--|---|-------------------------|-------------------------------------|-----------------------|--|---|---------------------------|-----------|--|--------------|--------------|--------|--------------|--------------------------|-------------|---------------|-------------|
| | | | | Project Impai Environmental/Natural Features Cultural/Eco | | | nemic Impact | Environmental Justice (0-10 Points) | | Constru | etability | Mobility and Implementation Travel Benefits (0-45 Points) | | | | | | | | |
| | S | 1 | | ı, | (0-10 Points) | ä | | (0-20) | Paints) | l tig | (0-10) | Points) | (0-15 | Points) | | 3 | (0.46) | Protesta) | | В |
| a | 2030 LRTP Project ID | Facility | Description | Wetlands 101 Certificat Sites | Voluntary Remediatio | Hazardous Wastel Superfund Si | Energency Services | Churches Cemeteries | ParturHistor Resources Protected La | Lend Uses Comomic I mg | Minerity | Low Incom- | Possibility. | Public Suppo | Bashiy | Intermodal U | Relief of Congression | Total Volum | E consectivit | Connectivit |
| Operations | /Design Imp | | | | | | | | | - | | | | | | | | | | |
| K1 | KC-4* | US 119 (Corridor G) | From US 60 (MacCorkle Avenue) to WY 601 (Jefferson Road). Use access management to improve mobility and safety | 0 | 0 | • | • | 0 | 0 | 0 | 0 | 0 | 0 | 0 | • | 0 | • | • | 0 | 0 |
| K2 | KC-2* | | From US 119 (Corridor G) to CR 21 (Kanawha Turnpike): Use access management to improve mobility and safety | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | • | • | • | • | 0 | 0 |
| К3 | KC-2* | WV 601 (Jellerson Road) | From CR 21 (Kanawha Turmpike) to US 60 (MacCorkle Avenue): Use access management to improve mobility and safety | 0 | 0 | 0 | • | 0 | 0 | 0 | 0 | 0 | 0 | 0 | • | • | • | • | 0 | 0 |
| P1 | | W V 34 | From Interstate 64 to Crooked Creek Road: Use access management to improve mobility and safety | 0 | 0 | 0 | 0 | 0 | 0 | • | 0 | 0 | 0 | | 0 | 0 | • | 0 | • | 0 |
| K4 | KC-9 | Interstate 64 at Oakwood Road Interchange | From US 60 (Washington Street) to WV 61 (MacCorkle Avenue): Improve weave section of interchange | • | 0 | • | 0 | 0 | 0 | 0 | 0 | • | 0 | • | 0 | • | • | 0 | 0 | 0 |
| K5 | KC-11* | | From CR 81 (Kellys Creek Road) to start of 4-lane section (by Admiral TJLopez Bridge): Use access management to improve mobility and safety | 0 | 0 | 0 | 0 | 0 | 0 | • | 0 | • | 0 | • | • | 0 | • | • | 0 | 0 |
| P2 | | CR 33 (Teays Valley Road) | From WV 34 split to Hurricane Creek Road: Use access management to improve mobility and safety | 0 | • | 0 | • | • | • | 0 | 0 | 0 | 0 | 0 | • | 0 | • | • | • | 0 |
| K6 | KC-10 | | From Kanawha Terrace to US 60 (MacCorkle Avenue): Grade separated railroad crossing improvements | 0 | 0 | 0 | 0 | 0 | • | 0 | 0 | 0 | 0 | | • | • | • | • | 0 | 0 |
| P8 | PC-6* | | From St. Albans Interchange to WV 34: Use access management to improve mobility and safety | 0 | 0 | 0 | • | • | 0 | 0 | 0 | 0 | 0 | 0 | • | • | • | • | • | 0 |
| KT | | US 60 (Dupont Avenue) | From end of 2-lane section (by Admiral TJ Lopez Bridge) to Fairview Drive: Use access management to improve mobility and safety | 0 | 0 | • | • | • | 0 | 0 | 0 | • | 0 | • | • | 0 | • | • | 0 | 0 |
| P4 | PC-6 | WV 817 (Winfield Road - Old US 35) | From Planters Road to Winfield Bridge (WV 34): Use access management to improve mobility and safety | 0 | 0 | 0 | • | 0 | • | 0 | 0 | 0 | 0 | • | 0 | • | • | • | • | • |
| K8 | KC-6* | WV 62 (West Washington Street) | From WV 25 (Dumbar Avenue) to WV 501 (Big Tyler Road): Use access management to improve mobility and safety | 0 | 0 | 0 | • | • | 0 | 0 | 0 | • | 0 | • | | 0 | • | • | • | 0 |
| P5 | 9 | CR 19 (Hurricane Creek Road) | From Teays Valley Road to Interstate 64: Use access management to improve mobility and safety | 0 | • | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | • | • | • | • | • | • | • |
| Expand Exi | eting | | | | | | | | | | | | | | | | | | | |
| P6 | PC-7* | | From WV 34 to Cabell County line: Widen to 6-lanes | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | • | 0 | • | • | 0 | | 0 | 0 |
| K1A | KC-4* | US 119 (GOTTAIOT G) | From US 60 (MacCorkle Avenue) to WV 601 (Jefferson Road): Widen to 6-lanes and implement mid and long-term recommendations for the facility | • | 0 | • | • | 0 | 0 | 0 | 0 | 0 | • | 0 | • | 0 | 0 | • | 0 | 0 |
| KSA | KC-2* | WV 601 (Jefferson Road) | From CR 21 (Kanawha Turnpike) to US 60 (MacCorkle Avenue): Widen to 4-lanes with a median | • | 0 | 0 | • | 0 | 0 | 0 | 0 | 0 | • | 0 | • | • | 0 | • | 0 | 0 |
| K2A | KC-2* | WV 601 (Jefferson Road) | From US 119 (Corridor G) to GR 21 (Kanawha Turmpike): Widen to 4-lanes with a median | • | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | • | 0 | • | • | 0 | • | 0 | 0 |
| P7 | PC-4 | Interstate 64 | From WV 25 (1st Avenue) to New US 35: Widen to 6 lanes, Replace Nitro Bridge | | 0 | • | 0 | 0 | 0 | 0 | 0 | 0 | • | 0 | • | • | 0 | 0 | 0 | 0 |
| K9 | KC-12 | WV 114 (Greenbrier Street) | From Airport Road to CR 46 (Rutledge Road): Widen to 3-lanes with a two-way left-turn lane | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | • | • | • | • | 0 | • | • | • | 0 |
| K10 | KC-6 | | From Six Mile Hollow Road to Interstate 64: Widen to 3-lanes on steep grades to provide truck passing lanes | 0 | 0 | 0 | 0 | • | 0 | • | 0 | • | • | • | • | 0 | • | • | 0 | 0 |
| P8 | PC-10 | WV 25 (1st Avenue) | From Interstate 64 to WV 62: Widen to 3 lanes with a two way left-turn lane, and use access management to increase mobility and safety | • | 0 | • | • | 0 | 0 | 0 | 0 | • | • | • | • | 0 | • | • | 0 | 0 |
| KSA | KC-11* | US 60 (Dupont Avenue) | From CR 81 (Kellys Creek Road) to start of 4 lane section (by Admiral TJ Lopez Bridge): Widen to 4 lanes divided | • | 0 | 0 | 0 | 0 | 0 | • | 0 | • | • | | • | 0 | • | | 0 | 0 |
| KSA | KC-6* | WV 62 (West Washington Street) | From WV 25 (Dunbar Avenue) to WV 501 (Big Tyler Road): Widen to 9-lanes with a two-way left turn lane | • | 0 | 0 | • | • | 0 | 0 | 0 | • | • | • | • | 0 | 0 | • | • | 0 |
| P9 | PC9 | WV 62 | From WV 25 (1st Avenue) to Heizer Creek Road: Widen to 3-lanes with a two-way left-turn lane, and use access management to increase inchility and safety | • | 0 | • | • | 0 | 0 | • | 0 | • | • | • | • | 0 | • | • | • | 0 |
| P10 | PC-8 | WV 62 (Rocsevelt Boulevard) | From East Fir Street to Nutmeg Street (Town of Eleanor): Widen to 3-lanes with a two-way left-turn lane | • | • | 0 | • | 0 | • | • | 0 | 0 | • | ٠ | • | • | • | ٠ | • | 0 |
| New Locatio | ew Location | | | | | | | | | | | | | | | | | | | |
| K12 | KC-15 | St. Albans Bridge (Henderson Bridge - Center Street) | From WV 25 (1st Avenue S.) to US 60 (MacCorkle Avenue): Construct a 4-lane bridge | • | 0 | • | 0 | 0 | 0 | 0 | 0 | • | • | 0 | • | 0 | 0 | • | 0 | 0 |
| P11 | PC5 | New US 35 | From WV 34 to the Mason County line: Construct 4 lane, median divided highway | • | 0 | 0 | 0 | 0 | 0 | 0 | 0 | • | • | 0 | • | • | 0 | • | 0 | 0 |

What's Next

- Exploring alternative funding sources
 - Tolling
 - Grant initiatives
 - CMAQ
- Moving key recommendations forward
 - Teays Valley area
 - St. Albans bridge and underpass
 - US 35





Tim Padgett, P.E.

TRAVEL DEMAND MODELING






Model Background

- EMME/2 Model with various upgrades and updates over time for planning work
- In 2008, Caliper Corporation converted the existing model to the TransCAD platform
- Caliper delivered a fully functional model, however it was not calibrated/validated therefore it couldn't be used for LRTP update work
- KHA, with assistance from RIC, performed calibration/validation, data updates, added additional model analysis years and updated the model interface






TransCAD Update Process

- Consistency check of parameters and input data from existing EMME/2 model to new TransCAD model
 - Model Network
 - SE Data Inputs
 - Traffic Counts
- Baseline 2000 model run
- Model calibration











Baseline 2000 Model Run

- As compared to counts, the baseline 2000 model run loading was high
- Overall loading 21% high
 - Freeways 22% high
 - Principal Arterials 32% high
 - Minor Arterials 20% high
 - Collectors 4% high





0



Model Calibration

- Trip Generation, Trip Distribution and Assignment checks and comparisons
 - Trip Generation
 - IE/EI trips were getting doubled in the time-of-day step
 - External station calculation was incorrect (model loading 34,000 traffic count 28,000)
 - Trip Distribution
 - Trip lengths were no longer calibrated to observed information
 - Assignment
 - Link level calibration





Final Calibration Table

| Model Calib | ration/Va | alidation | Summary |
|-------------|-----------|-----------|---------|
|-------------|-----------|-----------|---------|

| Assigned Volumes by Facility Classification | | | | | | | | | | |
|---|--------------|--------------------|---------------------|--|--|--|--|--|--|--|
| | | | | | | | | | | |
| Category | | EMME/2 Calibration | TransCAD Validation | | | | | | | |
| Freeway/Interstate | +/- 7% | 4.5% | 1.0% | | | | | | | |
| Major Arterial | +/- 10% | -1.6% | 0.0% | | | | | | | |
| Minor Arterial | +/- 15% | -15.6% | -10.0% | | | | | | | |
| Collector/Local | +/- 25% | -10.7% | -3.0% | | | | | | | |
| | | | | | | | | | | |
| Assigned Volumes by Volume Group | | | | | | | | | | |
| Category | FHWA Target | EMME/2 Calibration | TransCAD Validation | | | | | | | |
| <1000 | +/- 200% | 15.2% | 33.0% | | | | | | | |
| 1000-2500 | +/- 100% | -14.9% | 10.0% | | | | | | | |
| 2501-5000 | +/- 50% | -19.0% | -10.0% | | | | | | | |
| 5001-10000 | +/- 25% | -6.4% | -8.0% | | | | | | | |
| 1001-25000 | +/- 20% | -1.8% | -3.0% | | | | | | | |
| 25001-50000 | +/- 15% | 4.5% | 1.0% | | | | | | | |
| | | | | | | | | | | |
| >50000 | +/- 10% | -7.2% | -8.0% | | | | | | | |
| Total | +/- 5% | -3.6% | -2.0% | | | | | | | |
| | | | | | | | | | | |
| | Screenline S | ummary | | | | | | | | |
| Screenline | FHWA Target | EMME/2 Calibration | TransCAD Validation | | | | | | | |
| Kanawah River | +/- 5% | 2.3% | 1.0% | | | | | | | |
| Putnam/Kanawha County Line | +/- 5% | 1.7% | 11.0% | | | | | | | |
| Kanawha East | +/- 5% | -4.4% | -6.0% | | | | | | | |
| North Kanawha | +/- 5% | | -5.0% | | | | | | | |
| Kanawha West | +/- 5% | | -3.0% | | | | | | | |
| Kanawha Southwest | +/- 5% | 7.7% | 9.0% | | | | | | | |
| | | | | | | | | | | |
| Other Summaries | | | | | | | | | | |
| Category | FHWA Target | EMME/2 Calibration | TransCAD Validation | | | | | | | |
| RMSE Summary | 35% | 30.1% | 22.6% | | | | | | | |
| R2 Summary | 0.8 | 0.955 | 0.949 | | | | | | | |





Final Model

- Model years of 2000, 2002, 2007, 2009, 2010, 2013, 2015, 2018, 2020, 2025, 2030, 2035, and 2040
- Revised model interface
 - More easily set-up the model
 - More easily manage scenarios
 - View all model input/output files on one screen
- Provided RIC with model files, model documentation and model training





Final Model Interface







Model Training

- Morning (9:00-11:30) Model Overview
 - Installing the RIC Model
 - Introduction to the RIC Model Interface
 - Scenario Settings
 - Input and Output Files
 - Additional Interface Tools
- Afternoon (1:00-4:00) Applying the RIC Model
 - Editing Data
 - Scenario Management and Alternatives Analysis





Model Update Benefits

- Ease of use for day-to-day applications
- Interface providing tools for quick editing and results
- Documentation with background, tools, and tips
- On-site model training, explaining setup and everyday uses
- Easier integration with other statewide modeling and planning efforts







Regional Intergovernmental Council LONG RANGE TRANSPORTATION PLAN AND TRAVEL DEMAND MODEL

Tuesday, October 26, 2010



Base

Kimley-Horn and Associates, Inc.

