Market Street Bridge

"A picture is worth a thousand Words"




The success of the Market Street Bridge,

The top 10 list

How do you know??

The project was presented at the 2012 International Bridge Conference.



HE MARKET STREET BRIDGE, which crosses the Ohio River to link West Virginia and Ohio, had been in need of rehabilitation for some time. But that need became more pressing in 2009, when one - communities it connects. of the two other bridges that spanned the river to County, Ohio, was closed. After swift action by local and state leaders, a team of engineers from Burgess

as superimposing repair notes on plan photographs to meet an accelerated design schedule and transform the failing bridge, which is more than 100 years old, into an icon of the

A banker in Steubenville, Ohio, by the name of Dohrman. link Brooke County, West Virginia, with Jefferson J. Sinclair constructed the Market Street Bridge in 1905 to serve as a gateway for Steubenville residents who were interested in obtaining jobs at the tin mill that was being de-& Niple, Inc. (D&N), an engineering firm based in — veloped across the river. The 1,794 fr long ruble suspension. Columbus, Ohio, used such innovative techniques - bridge, stiffened by a Warren through cross, carried workers

Thank you letter from City Of Steubenville, OH



David M. LalichCouncilman

119 Aberdeen Road Steubenville, Ohio 43952 Phone: 740.266.6070 123 South Third Street Steubenville, Ohio 43952 Phone: 740.283.6000 ext. 2100 Email: council@cityofsteubenville.us

SEC-info

January 31, 2012

CC:CH HO

Secretary of Transportation Paul A. Mattox, Jr. 1900 Kanawha Blvd. East Building 5 Charleston, WV 25305

Dear Secretary Mattox:

14 2.29.12

On behalf of the City Council, City Administration, and citizens of the City of Steubenville we would like to take this opportunity to thank you for the rehabilitation of the Market Street Bridge that spans the beautiful Ohio River between the States of Ohio and West Virginia.

The span lends itself to economic opportunities on both sides of the river and we are greatly appreciative of all your hard work and investment.

Sincerely

David M. Lalich

Sixth Ward Councilman Chairman, Economic

Development Committee

Steubenville City Government

DML/plo



Thank you letters from Ohio residents

From: Michelle

[mailto:mikkig0104@att.net]

Sent: Tuesday, December 27, 2011 5:57 PM


To: DOT Secretary

Subject: Market Street Bridge

Mr. Mattox:

I am a resident of Steubenville, OH and I wanted you to know that I appreciate all that was done to make the Market Street Bridge look so beautiful. I do not live close enough to the bridge to view it as often as I would like; however, I work downtown and can see it from the building in which I work. I have found myself driving downtown Steubenville just to see the bridge lit at night. With so much negative news at the present time, the updated and decorated bridge is certainly a positive news item. I have heard nothing but positive comments about it. Thanks again for all that you and many others did to bring this about. It is appreciated by not only West Virginia residents but also Ohio residents. Michelle Groninger

Ribbon cutting ceremony



Market Street Bridge

RIBBON CUTTING CEREMONY
DECEMBER 7, 2011

Secretary Mattox speaks at ceremony




Governor Tomblin speaks at ceremony





Project engineer gets picture with the Governor



And The Number 1 Reasonis


The Project is still a buzz nearly two years after the completion date of the contract

















Bent 5 bearing















The State of Ohio closed the Fort Steubenville Bridge in 2009, which is less than two miles north of the Market Street bridge and reported that it would be demolished.

Around the same time the WVDOT was planning a new bridge about 10 miles south of the Market Street Bridge. Burgess and Niple's bridge inspection revealed the bridge was in need of major repairs.

The first thought was to:



However

Local leaders banned together and then Governor Joe Manchin pledged the bridge would be repaired.

Thanks to The American Recovery Act Money was available for the repairs.

In order to meet the deadline for funding Burgess and Niple expedited the plans for the rehabilitation.

A Good Candidate for Rehab?




Deciding Factors

- 2 of 3 Bridges Remain
 - * Increased Congestion
- * Traffic Served < 5 tons
- * Cost versus Benefit
 - * Rehab = \$10 million
 - New Bridge = \$100+ million
- * Future Cost vs. Service Life










The Design Phase

- June 1, 2009 Field Work Begins
 2 weeks
- June 14, 2009 Start Design Work
 10 weeks
- August 31, 2009 Submit Bid Set
- Streamlined Reviewsby WVDOT
- * Project FTP Site



Field Inspection







Tower Bracing Inspection



Strand Inspection



Cable Inspection



Tower Rappelling



Inspection Photos converted to Rehabilitation Plans



Field Inspection

- Measure & Mark on Bridge
- Photographs Square & Overall



Using Photographs in Rehab Plans

- * Insert as Raster Reference in Microstation
- * Add Notation and Details Pertaining to Repairs




Design Benefits

Inspection findings are well documented

Saves detailing of items that don't need hard dimensions

 Allows engineer to focus more time on typical details, procedures, and specs

* Each location can be shown



EXCAVATE SOIL. CLEAN & PAINT ALL EXPOSED EYEBARS. INSTALL CONCRETE W/ 12" CLEAR ALL AROUND EYEBARS

LOOKING SW @ OHIO ANCHORAGE

EXCAVATED SOIL SHALL BE WAISTED AROUND PLACED CONCRETE AND SLOPED TO DRAIN SURFACE WATER AWAY FROM THE EYEBARS. EXCAVATION SHALL BE BY HAND TOOLS. SEED AND MULCH TO FINISHED CONDITION SUITABLE FOR LAWN MOWER. - BOTTOM OF CONCRETE TO BE 12 BELOW LOWE EYEBAR AT INTERSECTION WITH ANCHOR

REMOVE METAL AROUND MAN C. CLEAN & PANT & REPLACE ME COVERING IN-KIN PANEL POINTS PANEL POINTS




TYPICAL TOWER SADDLE CASTING BELOW CAP

SHOWN IN RAISED POSITION FOR INSPECTION


Construction Benefits


- Contractor can see the existing conditions
- Clearly Communicates the Intent of the Repair
- Post-Repair Photo to Document As-Built Condition



LOOKING S @ ROCKER POST @ FB20 DS

Allows 3-D Perspective






- GRIND WELDS FLUSH & ADD PLATES PER REPAIR TYPE TI5 (TYP.) (REPAIR TYPE TI6 SIMILAR AT ABOVE LOCATIONS)


LOOKING NE @ SE COLUMN, OHIO TOWER. DS SMILAR AT OTHER LOCATIONS

Challenges

- Adjustment of CAD Standards
- * Full-Size Color Plots
- * Reproducible Mylars
- * Ability to Visualize in 3-D




A picture is worth a thousand...









Rocker Post Removal






LOOKING S @ ROCKER POST @ FB20 DS

VIEW LOOKING NORTH
SCALE: 1½" - 1'-0"




Removal for Suspender Retrofits



REMOVE VERTICAL LEG OF
FLOORBEAM REINFORCING ANGLES,
TRUSS ANGLES, PLATE, RIVETS
THROUGH STIFFENING CHORD
FLANGE, PACK RUST &
EXTRANEOUS STEEL TO PROVIDE
OPENING FOR 2"x3¾"x9"
CONNECTION BAR AND
SEAT FOR CATCHER BEAM

- REMOVE FASTENERS FROM LATERAL BRACING AS NECESSARY TO PROVIDE FLAT SURFACE FOR SHIM PLATE




DOWNSTREAM END FACING EAST HT

REMOVE STUBS OF TRUSS ANGLES,
PORTION OF TRUSS WEB, PORTIONS
OF FLOORBEAM STIFFENING PLATE
AND ANY OTHER EXTRANEOUS STEEL,
GRIND RESULTING OPENING SMOOTH
TO ACCOMODATE 2"x3¾"x 9"
CONNECTION BAR, TYPICAL AT
FLOORBEAMS 2, 3, 76, 77 & 78

CONNECTION BAR REMOVALS

FLOORBEAM 3 REMOVAL DETAIL SHOWN, FLOORBEAMS 2, 76, 77 & 78 SMILAR







Si




Structural Model




Tower Containment



Truss Containment






Construction Load Limitations

LIMIT OF CONSTRUCTION LOADS


AT NO TIME SHALL THE TOTAL GROSS WEIGHT OF ANY ONE VEHICLE, OR THE TOTAL WEIGHT OF STORED MATERIAL, OR COMBINATIONS THEREOF EXCEED 10 TONS AT ANY ONE LOCATION ON THE BRIDGE. A TOTAL OF THREE SUCH AREAS ARE PERMITTED ON THE BRIDGE WITH A MINIMUM CLEAR SPACING OF 100 FEET BETWEEN AREAS. AT NO TIME SHALL THE TOTAL GROSS WEIGHT OF ALL VEHICLES PLUS THE WEIGHT OF ALL STORED MATERIAL EXCEED 30 TONS.



Construction Load Limitations

LIMIT OF CONSTRUCTION LOADS

AT NO TIME SHALL THE TOTAL GROSS WEIGHT OF ANY ONE VEHICLE, OR THE TOTAL WEIGHT OF STORED MATERIAL, OR COMBINATIONS THEREOF EXCEED 10 TONS AT ANY ONE LOCATION ON THE BRIDGE. A TOTAL OF THREE SUCH AREAS ARE PERMITTED ON THE BRIDGE WITH A MINIMUM CLEAR SPACING OF 100 FEET BETWEEN AREAS. AT NO TIME SHALL THE TOTAL GROSS WEIGHT OF ALL VEHICLES PLUS THE WEIGHT OF ALL STORED MATERIAL EXCEED 30 TONS.





Market Street Bridge Facts

Built in 1905 to transport mill workers to WV by streetcar

Structure length: 1794 feet

Suspended length: 1200 feet

Suspended length between the 2 main towers: 680 feet

Roadway width: 20.7 feet

5 approach spans

Owned by the Steubenville Bridge Company

Purchased by WV in 1941 for \$ 1,300,000.00

Made \$ 400,000.00 worth of improvements for vehicle use

Place toll on bridge until 1953 to help pay for the repairs

Numerous upgrade made to the bridge

Market Street Bridge

Contractor: Albern & Associates / Kokosing

Designer: Burgess and Niple

Contract Bid: \$13,741,000.00

Change orders: \$1,112,369.78

Consultant inspection: G&O








All work performed from spider baskets











Attach tower plates to structure legs by welding or clips.
685 clips
1000 lf of weld

Three choices of repair:
Weld on interior of tower leg
Place 3x3 clip on interior
Weld on exterior of tower leg





New weld on tower plates

clips















