

Line	Comm Ln Desc	Qty	Unit Issue	Unit Price	Ln Total Or Contract Amount
1	63210053 Tripp Lite UPS	1.00000	EA	7986.000000	7986.00

Comm Code	Manufacturer	Specification	Model #
39121011			

Commodity Line Comments: Quoting an equivalent UPS system that exceeds the specification of the requested Tripp Lite UPS. This equivalent UPS system consist of (1) 10KVA and (1) 6KVA UPS for a total of 16KVA.

Extended Description:

Tripp Lite UPS Smart Online 208/240 & 120V 16kVA 11.2kW Double-Conversion UPS, 8U, Extended Run, Network Card Slot, USB, DB9, Bypass, NEMA Outlets; PN SU16000RT4U

XTREME POWER CONVERSION P91 5kW, 6kW, & 10kW

Online UPS // 208/230VAC or 208/120VAC

For more information, visit
www.xpcc.com/p91_5-10



Complete power protection in less space for high density loads

Designed for high density critical loads, the P91 delivers industry leading reliability, efficiency and flexibility.

P91 can be configured for online or ECO mode operation for efficiency of up to 99%. Output voltage and frequency are programmable to meet a wide range of USA and international requirements.

For distribution options, reference the XPDU at www.xpcc.com/XPDU

PRODUCT SNAPSHOT

- › Available models: 5kVA/5kW, 6kVA/6kW, 10kVA/10kW
- › Tower, 2-post, and 4-post rack mounting configurations
- › Unity power factor
- › UL 1778, cUL, FCC, RoHS, CE, TAA compliant
- › 3 years electronics, 3 years battery warranty (USA and Canada)

FEATURES

Unity output power factor—P91 systems provide more real capacity for high density loads

Efficient operation—up to 94% online or 99% ECO mode efficiency lowers energy consumption

Hot swappable battery—P91 optional battery packs are easy to replace without interrupting the load

Isolation transformer—optional transformer provides 240/120 or 208/120V output

Multiple communications capability—RS-232, USB, and optional Web/SNMP, Modbus, Relay/dry contact cards

XBDM—optional input/output distribution, maintenance bypass switch, each output receptacle is protected by a breaker

\$50,000 load protection policy—protection against damaged connected equipment

XTREME
Power Conversion®

Protect your business.

MODEL SELECTION GUIDE

For more information, visit www.xpcc.com/p91_5-10

MODEL NUMBER		P91-5K	P91-6K	P91-10K	
CAPACITY	Power rating	5kVA (5kW)	6kVA (6kW)	10kVA (10kW)	
INPUT	Voltage	110–300VAC*			
	Frequency	50/60Hz			
OUTPUT	Voltage	208/220/230/240VAC (208/120V or 240/120V with optional transformer)***			
	Frequency	50/60Hz ± 4Hz			
	THD (full load)	< 4%			
	Overload capacity	110% 10 min; 130% 1 min; > 130% 1 sec			
	Efficiency	Up to 94% online mode or 99% ECO mode			
BATTERY	Charger amps	1–4A			
	Nominal/float voltage	240/273VDC			
DIMENSIONS & WEIGHT	Dimensions (W x D x H)	17.2 x 23.6 x 3.5 in			
	Weight	33.1 lbs		39.7 lbs	
BYPASS DISTRIBUTION MODULE	Model	XBDM-P91A (5 or 6kVA)	XBDM-P91B	XBDM-P91C	XBDM-P91D
	Input connection	L6-30P with 6' cord	Terminal Blocks or optional line cord		
	Output connection	(2) L6-30R + (2) C19** each with breaker	Terminal block + L6-30R + (2) C19** each with breaker	Terminal block + L6-30R with breaker	(2) L6-30R each with breaker
ENVIRONMENT	Operating temperature	32–104°F (0–40°C)			
	Audible noise	< 55dBA		< 58dBA	
	Altitude	11,500 ft above sea level			
APPROVALS	UL 1778, cUL, FCC, RoHS, CE, TAA compliant				
WARRANTY	3 years electronics, 3 years battery warranty (USA and Canada)				
COMMUNICATIONS INTERFACE	RS-232, USB, EPO, intelligent slot for optional cards (Web/SNMP, relay/dry contact, modbus)				
INCLUDED IN BOX	Software CD, horizontal brackets, tower pedestals, USB cable				
AVAILABLE OPTIONS	5 year extended warranty, 4-post rail kit, 2-post shelf kit, 2U/3U isolation transformer				

*Depending on load level. **Optional locking C20 dongles; L6-30R, L6-20R, 6-20R. *** P91 capacity derates to 90% at 208V output voltage.

BATTERY PACK DATA & RUNTIMES

	Qty	1kW	2kW	3kW	4kW	5kW	6kW	7kW	8kW	9kW	10kW	
Model Number	BPXR2U240A	1 BP	53	27	15	11	7	5	4	4	3	2
Dimensions	17.2 x 27.4 x 3.5 in (2U)	2 BP	117	61	38	27	20	15	13	11	9	7
Battery Quantity/Type	(20) 12V 5AH Lead Acid	3 BP	171	100	62	43	33	27	22	18	15	13
Model Number	BPXR3U240A	1 BP	92	46	29	20	15	12	10	8	7	6
Dimensions	17.2 x 27.4 x 5.2 in (3U)	2 BP	182	106	66	47	36	29	24	20	18	15
Battery Quantity/Type	(20) 12V 580W Lead Acid	3 BP	287	151	107	76	58	47	39	33	29	25

Runtimes are shown in minutes and will vary based on battery age and site conditions. For longer runtimes please contact sales@xpcc.com or visit www.xpcc.com/selector/



X-TREME
Power Conversion®

Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

XPC EMEA / Rotterdam, NL / emea@xpcc.com

www.xpcc.com

©2020 Xtreme Power Conversion Corporation. All Rights Reserved. P915-10.01U (Rev 1/15/20)



XPD35

X-TREME

Power Conversion®

XPD-IT60A



230 Yuma Street
Denver, CO 80223



(800) 582-4524



sales@xpcc.com



www.xpcc.com

XPD-IT60A Product Overview



XPD-IT60A front view



XPD-IT60A rear view

208V (default) or 240V input
voltage selector switch

(12) 120V NEMA 5-15/20R
receptacles with 20A breakers

208V L6-30R
output cord

3ft, L6-30P Input cord –
connects to UPS output

XPD-IT60A Specifications

PRODUCT SPECIFICATIONS	
Model number	XPD-IT60A
Part number	90000407
Description	6kVA PDU with Isolation Transformer with 120V and 208V (or 240V) outputs
Capacity	5.8kW with 240V input (or 5kW at 208V); Maximum 120V load is 4kW
Input power connection	3 ft, L6-30P
Outlets	120V: (12) 5-15/20R; 208V: (1) L6-30R
Input voltage	208VAC default / 240VAC selectable
Output voltage	120V goes through the transformer, 208 or 240V is the same as the PDU input voltage and is passed around the transformer
Dimensions (W x D x H)	19.0" x 18.0" x 3.5" (2U)
Weight	137 lbs
List price	\$1,299.00