

Type V Pavement Markings

Material Code: 715.040.002
Effective: 1/22/2025
Contact: Gary.W.Mullins@wv.gov

| Manufacturer | Model | Lab Number |
|-------------------------------------|---|------------|
| 3M Corporation | 380-IES White or Yellow (Note 2) | 1393191 |
| Ennis Flint Inc. | Premark White or Yellow (Note 3) | 1393192 |
| Ennis Flint Inc. | Hot-Tape White or Yellow (Note 4) | 1393189 |
| Ozark Materials LLC / Ingevity Corp | Yellow or White Preformed Thermoplastic / Yellow or White CHOICE Preformed Thermoplastic (Note 3) | 1462424 |
| Geveko Markings Inc. | Optamark White or Yellow (Note 3) | 2100801 |
| Ozark Materials LLC / Ingevity Corp | Yellow or White Pre-formed 70 BPN / Yellow or White CHOICE HSR Preformed (Note 5) | 1462425 |
| Ennis Flint Inc. | Premark Vizigrip White or Yellow (Note 6) | 1393193 |
| Crown USA, Inc. | Tuff Mark White or Yellow (Note 3) | 2200395 |
| Crown USA, Inc. | Tuff Mark Tuff Grip White or Yellow (Note 6) | 2200396 |
| PREFORM LLC | 715-4-2 Preformed Traffic Markings TY V White or Yellow (Note 6) | 2400246 |
| Gentem Inc. | Preformed Thermoplastic (Note 3) | 2400270 |

Notes:

1 - Type V markings include the following applications:

- Transverse markings, which includes intersection markings such as crosswalk lines and yield triangles, symbols such turn arrows and bike lane markings, legends such as railroad and ONLY markings, and diagonal stripes for gore areas and lane shunts
- Longitudinal markings, which includes channelizing lines, edge lines, barrier lines, and lane lines

Materials listed on this APL shall only be utilized for the applications that they are noted as being approved for. Any product specific application requirements noted shall be followed. Enhanced skid resistant material shall be used for all crosswalk stripes and any other markings noted in the project plans. Only materials noted herein as being an enhanced skid resistant material shall be used for these applications.

2 - This product is approved for all longitudinal markings. The only transverse marking applications this product may be used for are diagonal stripes in gore areas and lane shunts.

3 - This product is approved for all longitudinal and transverse markings.

4 - This product is approved for all longitudinal and transverse markings. When applying this material, the road surface shall be pre-heated to 400 degrees Fahrenheit and the material shall be heated to 400 degrees Fahrenheit. Both shall be verified with a infrared heat thermometer.

5 - This product is approved for all longitudinal and transverse markings required to be an enhanced skid resistant material. The material utilized shall be the same as the manufacturer's standard material also listed on this APL, with additional components added to meet a BPN measurement of 70, as offered as an option by the manufacturer.

6 - This product is approved for all longitudinal and transverse markings required to be an enhanced skid resistant material.