

WEST VIRGINIA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING DIVISION

MATERIALS PROCEDURE

NUCLEAR FIELD DENSITY - MOISTURE TEST FOR RANDOM MATERIAL HAVING
LESS THAN 40% OF + 3/4 INCH MATERIAL

1. PURPOSE

- 1.1 This procedure is to determine the density and moisture content of random materials.
-

2. SCOPE

- 2.1 This method of testing is applicable to random materials used for embankments, subgrades, backfill, and soil cement base courses.
-

3. REFERENCED DOCUMENTS

- 3.1 *AASHTO Standards:*
3.1.1 AASHTO T99, Method C
- 3.2 *Materials Procedures:*
3.2.1 MP 712.21.26
3.2.2 MP 717.04.21U.S.
-

4. EQUIPMENT

- 4.1 One complete nuclear density-moisture gauge unit meeting the requirements specified in MP 717.04.21. A copy of the manufacturer's print-out of standard counts is to be included.
- 4.2 One 1/30 ft³ proctor mold assembly with a 5.5 LB rammer meeting the requirements of AASHTO T99.
- 4.3 One steel foundation plate having minimum dimensions of 15 in. x 15 in. x 5/8 in. or a 200 LB block of concrete.
- 4.4 One extruder for removing specimens from proctor mold.
- 4.5 One balance having a capacity of at least 10 kg and sensitive to 1.0 g.
- 4.6 One stove for drying moisture samples.
- 4.7 One 32 oz. ballpeen hammer or equivalent.

- 4.8 Two pans with a capacity to hold 10 LB of material.
- 4.9 One pan suitable for drying moisture samples.
- 4.10 One wire brush
- 4.11 One 3/4 in. U.S. Standard Sieve
- 4.12 One scoop
- 4.13 One ruler or tape measure
- 4.14 One measuring tape (should be a minimum of 50 ft)
- 4.15 One paint brush approximately 2 in wide
- 4.16 One 18 in. chisel or equivalent
- 4.17 One draw knife
- 4.18 T-316 data sheets and attached tables
- 4.19 One appropriate vehicle for transporting nuclear gauge and test equipment

5. PERSONNEL TRAINING

- 5.1 All personnel performing the testing must have the minimum training requirements specified in MP 717.04.21.
- 5.2 All personnel must know and follow the requirements of the Nuclear Regulatory Commission.

6. ROUNDING OF DATA

- 6.1 Test values and calculations are to be rounded according to the following procedure:
 - 6.1.1 If the figure following the last significant number to be retained is five or larger, increase the last significant number to be retained by one.

- 6.1.2 If the figure following the last significant number to be retained is less than five, the significant number is left unchanged.
- 6.1.3 Test values and calculations shall be rounded to the following nearest significant digit.

Station Number:	1 ft.
Offset:	1 ft.
Lift Thickness:	1/2 in.
Depth Below Grade:	1 ft.
Dry Density (DA):	1 LB/ft ³
Moisture (MA):	1 LB/ft ³
Dry Density - 3/4 in. material (DB):	1 LB/ft ³
Moisture (MB):	1%
Excavated Material + Pan (CA):	1 g
Pan (CB):	1 g
Excavated Material (CC):	1 g
+3/4 in. Material + Pan (CD):	1 g
Pan (CE):	1 g
+3/4 in. Material (CF):	1 g
+3/4 in. Material (CG):	1%
Weight of Soil + Mold (PA):	1 g
Mold (PC):	1 g
Weight of Soil (PD):	1 g
Wet Density (PE):	1 LB/ft ³
Dry Density (PF):	1 LB/ft ³
Wet Weight + Pan (SA):	1 g
Pan (SB):	1 g
Wet Weight (SC):	1 g
Dry Weight + Pan (SD):	1 g
Dry Weight (SE):	1 g
Moisture (SF):	1 g
Moisture (SG):	1%
Optimum Moisture (OA):	1%
Maximum Density (DC):	1 LB/ft ³
Relative Density (DE):	1%
Average DE (X):	0.1%
Target (T):	1%
Quality Index (L):	0.01
Within Tolerance (DF):	1%
Minimum Percent for 100% Pay (DG):	1%

7. PREPARATION FOR TESTING

- 7.1 Weigh the pans and proctor mold and record the weights on the sides of the equipment. The weights shall be checked at least on a monthly basis.
- 7.2 All test data is to be recorded on the attached form T-316.

- 7.3 Standardization of the nuclear gauge
 - 7.3.1 Warm up the gauge according to the manufacturer's specifications.
 - 7.3.2 Standardization of the gauge must be performed away from metal and other objects.
 - 7.3.3 Clean the top of the standard block and the bottom of the gauge with a cloth.
 - 7.3.4 Place the gauge on the standard block with the gauge turned the correct way. For the Troxler 3400 series gauges, the scaler end of the gauge must be tight against the standard block flange.
 - 7.3.5 Make the necessary adjustments on the gauge and perform a standardization according to the manufacturer's specifications.
 - 7.3.6 Compare the standard counts to the manufacturer's standard counts. The standard count must be within $\pm 2\%$ for density and $\pm 4\%$ for moisture from the manufacturer's standards.
 - 7.3.7 If the gauge is not within the specified tolerances for either moisture or density, repeat Section 7.3.5 - 7.3.6. If the gauge will not standardize for either moisture or density after 4 attempts, a different gauge shall be used. The gauge which failed to standardize may be used again in the future if the procedure referenced in Section 5.2.10 of MP 717.04.21 is followed and the gauge is found to be stable.
 - 7.3.8 When a gauge is used for testing pipe or structure backfill in a trench, first check the standardization of the gauge according to Sections 7.3.1 - 7.3.6. If the gauge is functioning properly, then standardize the gauge in the trench. The standard counts in the trench are used for testing in the trench only and the tolerances shall not be applied to the standard counts taken in the trench. When the gauge is moved to a non-trench condition for testing, new standard counts shall be required.
 - 7.3.9 Gauges shall be standardized before testing and at least every four hours during testing.
- 7.4 Record the contract ID, project number, item number, etc.
- 7.5 The lot number has the following prefix letter designations based on the use of the material:

Embankment -	F
Subgrade -	S
Base -	B
Pipe and Structure Backfill -	P
- 7.6 Randomly locate the test site according to MP 712.21.26.

8. PROCEDURE

- 8.1 Density and moisture determination
 - 8.1.1 Smooth the test site selected for testing. Fill any voids in the surface using the fines scraped from the surface. Avoid adding excessive fines that would form a build-up on the surface (no more than 1/8 in.).
 - 8.1.2 Place the guide plate on the test site. Next, place the drive rod in the plate guide and while standing on the plate, drive the rod at least 2 in. deeper than the location where the end of the gauge source rod will be when testing. The gauge source rod can be extended in 2 in. increments. The source rod must be as deep as possible within the lift but must not extend beyond the lift. For example, a 5 in. (125 mm) lift shall be tested with the source rod in the 4 in. position and the hole shall be 6 in. deep. Carefully remove the drive rod to prevent material from falling into the hole.
 - 8.1.3 Place the gauge over the test site and insert the source rod to the desired depth. Pull the gauge tight against the side of the hole toward the scaler. Make sure the gauge is sitting flush on the material.
 - 8.1.4 Take a one-minute density and moisture reading. Record the dry density (DA) and moisture (MA).
- 8.2 Determination of the percent of + 3/4 in. material
 - 8.2.1 Excavate approximately 4500 g (10 LB) of material immediately beneath the test site. Excavate the material from the test hole toward the scaler end of the gauge and to the depth of the position where the source rod was located. Keep the excavated material covered to prevent moisture loss.
 - 8.2.2 Zero the scales. The scales shall be located in an enclosed area of the vehicle that is protected from air movement. The scales are to be checked for zero before each weighing. Weigh the excavated material (CA).
 - 8.2.3 The material weighed in 8.2.2 shall be passed over the 3/4 in. sieve. Break up any clumps of soil that are retained on the sieve and clean the fines from the + 3/4 in. material.
 - 8.2.4 Weigh the +3/4 in. material (CD) obtained in 8.2.3.
 - 8.2.5 Calculate the percent of +3/4 in. material (CG) by using the equations on form T-316. If the percentage of +3/4 in. material is 40% or more, terminate the test. Refer to MP 717.04.21 for instructions

- 8.2.6 Determine the bulk specific gravity (CH) of the dominant +3/4 in. material by using the values from the following table:

Bulk Specific Gravity	
Soft Shale:	2.4
Hard Shale:	2.5
Sandstone:	2.5
Gravel:	2.6
Limestone:	2.7
Red Shale (Iron Bearing)	2.7

- 8.3 Determination of the dry density of the -3/4 in. material and percent field moisture.
- 8.3.1 The dry density of the -3/4 in. material (DB) shall be calculated by the equation on form T-316 or obtained from the tables in attachment 3 of this document, using the specific gravity of the + 3/4 in. material (CH), the total dry density (DA), and the percentage of + 3/4 in. material (CG).
- 8.3.2 Calculate the percent field moisture (MB) by the equation on form T-316.
- 8.4 One-point proctor
- 8.4.1 Place the proctor mold with collar and base attached on the foundation plate. The foundation plate must be firmly seated so that it does not rock when compacting the material. Mix the -3/4 in. material obtained in 8.2.3. Form a specimen by compacting the material in the mold in three approximately equal layers totaling a minimum of 4 1/2 in. and a maximum of 5 in. Each layer is compacted by 25 uniformly distributed blows with the metal rammer dropped freely from a height of 12 in. Stand on the edges of the mold base while compacting the specimen. The rammer must be held vertically.
- 8.4.2 After the specimen has been made, remove the extension collar. The sample must not extend more than 1/2 in. above nor be below the top of the mold. A new specimen shall be made if these tolerances are not met. Carefully trim the material flush with the top of the mold by using the draw knife. Fill any voids in the surface with the fines obtained from the trimming. Use the paint brush to clean the fines from the outside of the mold. Remove the mold base and by holding the mold vertically, visually check the bottom of the mold to determine if the material extends beyond the mold. Do not turn the mold upside down nor trim the bottom. If the material extends beyond the bottom of the mold, perform another specimen with special precautions to seat and tighten the mold to the base.
- 8.4.3 Weigh the soil plus mold (PA). Record the value in the first column of the one-point proctor section on Form T-316. Do not use the rerun column at this time.
- 8.4.4 Remove the specimen from the mold by using the extruder. Place the specimen back in the remaining -3/4 in. material.

- 8.4.5 Perform the calculations using the equations on the form T-316 to determine the dry density of the one-point proctor (PE).
- 8.5 Determination of the maximum density and optimum moisture
- 8.5.1 To determine the maximum density and optimum moisture, plot the percent field moisture (MB) and the dry density of the one-point proctor (PE) on the maximum density-optimum moisture table (attachment 2). The values at the intersection of the density line and moisture column are the maximum density (DC) and optimum moisture (OA). If there are no values given, the sample is either too wet or too dry to determine the maximum density and optimum moisture. When the plotted point is to the right of the maximum densities and optimum moistures, the sample is too wet and when the plotted value is to the left, the sample is too dry.
- 8.5.2 If the sample is found to be too wet, air dry the -3/4 in. material to decrease the moisture content to between four percentage points below optimum and optimum moisture. The sample is dried by spreading the sample on a non-absorbent surface. Do not dry the sample on a stove. If the sample is too dry, add water to increase the moisture content to between four percentage points below optimum and optimum moisture. Care shall be taken not to over dry or add too much water to the sample.
- 8.5.3 Rerun one-point proctor
- 8.5.3.1 Once the sample has been air dried or water added, thoroughly mix the sample, and perform another one-point proctor according to 8.4.1 - 8.4.4. Record the data in the second column (rerun) of the one-point proctor section on form T-316.
- 8.5.3.2 Calculate the wet density of the rerun one-point proctor (PE) by using the equations on form T-316.
- 8.5.4 Stove dried moisture
- 8.5.4.1 Scoop out a representative sample between 200 g and 400 g from the sample in 8.5.3.1. The moisture determination can be made in conjunction with making the rerun one-point proctor specimen. Place the sample in the pan for drying samples and determine the sample weight plus pan (SA).
- 8.5.4.2 Adjust the stove flame to a low heat so that the sample will not oxidize during drying. Occasionally stir the sample and be very careful not to lose any of the sample. Once the sample appears dry, weigh the sample, and record the weight. Place the sample back on the stove and dry for approximately two minutes. Weigh the sample and compare the two weights. The weights should be the same (constant). If there is a decrease in weight, reheat the sample again for two minutes and weigh. Continue this process until two consecutive weights are obtained. Record this weight as dry weight plus pan (SD).
- 8.5.4.3 By using the equations on form T-316, calculate the percent moisture (SG).

- 8.5.5 Use the percent moisture (SG) from the stove dried moisture to calculate the dry density of the rerun one-point proctor (PE).
- 8.5.6 Plot the dry density of the rerun one-point proctor (PE) and the percent stove dried moisture (SG) on the maximum density-optimum moisture table to obtain the maximum density (DC) and the optimum moisture (OA).

9. MOISTURE EVALUATION

- 9.1 Obtain the \pm moisture tolerance (OB) from the project's governing specifications. Normally this tolerance is +3/-4.
- 9.2 To determine the acceptable moisture range, add the plus tolerance and subtract the minus tolerance from the optimum moisture. The field moisture (MB) must be within this range for the moisture to meet specifications. If the moisture fails specifications, corrective action is required.

10. DENSITY EVALUATION

- 10.1 Calculate the percent relative density (DE) by the equation on form T-316.
- 10.2 If the percent relative density (DE) is 105 or more, the test results may be in error. Plot the dry density of the -3/4 in. material (DB) and the percent field moisture (MB) on the maximum density-optimum moisture table to check the validity of the test results. The plotted point should fall on or to the left of the darkened blocks (zero air voids). Another method of checking the test results is to calculate the maximum moisture content possible (zero air voids) by the following equation:

$$\text{Maximum moisture content possible (English)} = (62.4/\text{DB} - .373)100$$

When the test results are equal to or less than the above evaluation, the results are acceptable.

- 10.3 When the conditions in 10.2 are not met, perform another complete test, including a one-point proctor, at a new random location. The checks in 10.2 shall again be made if the test results are 105% or more. If the conditions in 10.2 are still not met, obtain a sample, and determine the specific gravity of both the +3/4 in. and -3/4 in. material, performed separately. Then recalculate the test results using the specific gravity of the +3/4 in. material to determine the dry density of the -3/4 in. material (DB). If the percent relative density is still 105% or more, perform the following calculation using the specific gravity of the -3/4 in. material.

$$\text{Maximum moisture content} = (62.4/\text{DB} - 1/\text{Sp. Gr.})100$$

The field moisture (MB) must be equal to or less than the maximum moisture content (new zero air voids). If the test results still appear to be invalid, an immediate investigation must be conducted.

11. LOT EVALUATION

- 11.1 Five tests are required for a lot evaluation. Each test shall be performed according to previous sections of this procedure.
- 11.2 Calculate the average relative density (x) for the five tests in the lot.
- 11.3 Obtain the target percentage of dry density (T) from the project's governing specifications.
- 11.4 Determine the range (R) of the relative densities (DE) by subtracting the smallest value from the largest.
- 11.5 Calculate the quality index (QL) by using the equation on form T-316.
- 11.6 Enter the table for estimating the percent of a lot within tolerance (attachment 1). Determine the percent within tolerance (DF) which corresponds to the QL value calculated in 11.5 above.
- 11.7 Obtain the minimum percent for 100% pay (DG) from the project's governing specifications.
- 11.8 For a lot to meet specifications for density, the percent within tolerance (DF) must be equal to or greater than the percent for 100% pay (DG). Corrective action is required to bring a failing lot into specification requirements.

12. GENERAL REQUIREMENTS

- 12.1 For a lot to meet specifications, the requirements in 9.2 and 11.8 must be met.
- 12.2 The maximum density, optimum moisture, and percentage of +3/4 in. material may be used for subsequent tests in a lot if the -3/4 in. material does not change. When the material changes, the determination of new control data is required. There must be at least one, one-point proctor, for each lot.
- 12.3 If the test results indicate that the material meets specifications and the material exhibits pumping or displacing action under the weight of construction equipment, obtain a sample of the material and determine the maximum density and optimum moisture according to AASHTO T99, Method C. Until the laboratory test results are obtained, the material in question shall be dried and re-compacted until the pumping stops. The area shall then be retested, and this moisture content used as the upper limit for moisture during the interim period.

MP 207.07.20
OCTOBER 1999
RECONFIRMED: JANUARY 4, 2023
PAGE 10 OF 10

- 12.4 During the compaction of soil cement base course, if the material starts to shear, cease rolling even though the required specifications for compaction are not met. The material is accepted for compaction and the proper documentation in the project's records shall be made.
- 12.5 Independent tests for similarity checks shall be recorded on form T-316. Use only the applicable sections of the form.



01/04/2023

Ronald L. Stanevich, P.E.
Director
Materials Control, Soils and Testing Division

MP 207.07.20 Steward – Aggregate Section

RLS:Mj

ATTACHMENTS

MP 207.07.20 – ATTACHMENT 1
 OCTOBER 1999
 RECONFIRMED: JANUARY 4, 2023
 PAGE 1 OF 1

Attachment 1 TABLE FOR ESTIMATING PERCENT OF LOT WITHIN TOLERANCE

Quality Index (QL) Positive Values	Percent Within Tolerance	Quality Index (QL) Negative Values	Percent Within Tolerance
.66	99	.00	50
.65	98	.01	49
.62	97	.02	48
.60	96	.04	47
.58	95	.05	46
.57	94	.06	45
.55	93	.07	44
.53	92	.08	43
.51	91	.09	42
.50	90	.10	41
.48	89	.11	40
.46	88	.13	39
.45	87	.14	38
.44	86	.15	37
.42	85	.16	36
.41	84	.17	35
.40	83	.18	34
.38	82	.19	33
.37	81	.21	32
.36	80	.22	31
.34	79	.23	30
.33	78	.24	29
.32	77	.25	28
.30	76	.27	27
.29	75	.28	26
.28	74	.29	25
.27	73	.30	24
.25	72	.32	23
.24	71	.33	22
.23	70	.34	21
.22	69	.36	20
.21	68	.37	19
.19	67	.38	18
.18	66	.40	17
.17	65	.41	16
.16	64	.42	15
.15	63	.44	14
.14	62	.45	13
.13	61	.46	12
.11	60	.48	11
.10	59	.50	10
.09	58	.51	9
.08	57	.53	8
.07	56	.55	7
.06	55	.57	6
.05	54	.58	5
.04	53	.60	4
.02	52	.62	3
.01	51	.63	2
.00	50	.66	1

Attachment 2

MAXIMUM DENSITY-OPTIMUM MOISTURE TABLE

DRY DENSITY OF ONE POINT PROCTOR

	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25									
130			131 9																										
129		131 9	130 9	129 9																									
128		130 9	130 9	128 10																									
127	131 9	130 9	128 10	127 10	127 10																								
126	131 9	130 9	128 10	127 10	126 10																								
125	130 9	128 10	127 10	126 10	125 10																								
124		128 10	126 10	125 11	125 11	124 11																							
123		127 10	126 10	124 11	123 11	123 11																							
122		126 10	125 11	124 11	123 11	122 12																							
121		126 11	125 11	123 12	122 12	121 12	121 12																						
120		125 11	124 11	122 12	121 12	120 12	120 12																						
119			123 12	122 12	120 12	120 12	119 13																						
118			122 12	120 12	120 12	119 13	118 13	118 13																					
117				120 12	119 13	118 13	117 13	117 13																					
116					119 13	118 13	117 13	117 13	116 14																				
115						118 13	117 13	116 14	116 14	115 14	115 14																		
114							117 13	116 14	116 14	115 14	114 14	114 14																	
113								116 14	115 14	114 14	114 14	113 15																	
112								115 14	115 14	113 15	113 15	112 15	112 15																
111									115 14	113 15	112 15	112 15	111 15	111 16															
110										113 15	112 15	112 15	111 16	111 16	110 16														
109										112 15	111 16	110 16	110 16	109 16	109 16														
108											111 16	110 16	110 16	109 16	109 17	108 17													
107											110 16	109 17	108 17	108 17	107 17	107 17													
106												109 17	108 17	107 17	107 17	106 18	106 18												
105												108 17	107 17	107 18	106 18	106 18	105 18												
104													107 17	106 18	105 18	105 18	104 19	104 19											
103													106 18	105 18	105 19	104 19	103 19	103 19	103 19										
102													105 18	105 19	104 19	103 19	103 20	102 20	102 20										
101														104 19	103 20	102 20	102 20	101 20	101 21	101 21									
100														103 19	102 20	101 20	101 21	100 21	100 21	100 21									
99															102 20	101 21	101 21	100 21	99 21	99 22	99 22								
98																100 21	100 21	99 22	99 22	98 22	98 22	98 22							
97																	100 21	99 21	99 22	98 22	97 22	97 23	97 23						
96																		99 22	98 22	98 22	97 23	96 23							
95																		99 22	98 23	97 23	97 23	96 24							
94																		98 22	97 23	96 24	95 24	94 24	94 24						
	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25									

PERCENT MOISTURE

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

1 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.4

DD	PERCENT of + 3/4 MATERIAL									
	1	2	3	4	5	6	7	8	9	10
80	79	79	78	78	77	77	76	75	75	74
81	80	80	79	79	78	78	77	77	76	75
82	81	81	80	80	79	79	78	78	77	76
83	83	82	81	81	80	80	79	79	78	78
84	84	83	83	82	81	81	80	80	79	79
85	85	84	84	83	83	82	81	81	80	80
86	86	85	85	84	84	83	83	82	81	81
87	87	86	86	85	85	84	84	83	83	82
88	88	87	87	86	86	85	85	84	84	83
89	89	88	88	87	87	86	86	85	85	84
90	90	89	89	88	88	87	87	86	86	85
91	91	90	90	89	89	88	88	87	87	86
92	92	91	91	90	90	89	89	89	88	88
93	93	92	92	91	91	91	90	90	89	89
94	94	93	93	92	92	92	91	91	90	90
95	95	94	94	93	93	93	92	92	91	91
96	96	95	95	95	94	94	93	93	92	92
97	97	96	96	96	95	95	94	94	94	93
98	98	97	97	97	96	96	95	95	95	94
99	99	98	98	98	97	97	97	96	96	95
100	100	99	99	99	98	98	98	97	97	96
101	101	100	100	100	99	99	99	98	98	98
102	102	101	101	101	100	100	100	99	99	99
103	103	102	102	102	101	101	101	100	100	100
104	104	103	103	103	103	102	102	102	101	101
105	105	104	104	104	104	103	103	103	102	102
106	106	105	105	105	105	104	104	104	103	103
107	107	106	106	106	106	105	105	105	105	104
108	108	108	107	107	107	106	106	106	106	105
109	109	109	108	108	108	108	107	107	107	106
110	110	110	109	109	109	109	108	108	108	108
111	111	111	110	110	110	110	109	109	109	109
112	112	112	111	111	111	111	111	110	110	110
113	113	113	112	112	112	112	112	111	111	111
114	114	114	113	113	113	113	113	112	112	112
115	115	115	114	114	114	114	114	114	113	113
116	116	116	116	115	115	115	115	115	114	114
117	117	117	117	116	116	116	116	116	116	115
118	118	118	118	117	117	117	117	117	117	116
119	119	119	119	118	118	118	118	118	118	118
120	120	120	120	120	119	119	119	119	119	119

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

2 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.4

DD	PERCENT of + 3/4 MATERIAL									
	1	2	3	4	5	6	7	8	9	10
121	121	121	121	121	120	120	120	120	120	120
122	122	122	122	122	121	121	121	121	121	121
123	123	123	123	123	123	122	122	122	122	122
124	124	124	124	124	124	124	123	123	123	123
125	125	125	125	125	125	125	124	124	124	124
126	126	126	126	126	126	126	126	125	125	125
127	127	127	127	127	127	127	127	127	127	126
128	128	128	128	128	128	128	128	128	128	128
129	129	129	129	129	129	129	129	129	129	129
130	130	130	130	130	130	130	130	130	130	130
131	131	131	131	131	131	131	131	131	131	131
132	132	132	132	132	132	132	132	132	132	132
133	133	133	133	133	133	133	133	133	133	133
134	134	134	134	134	134	134	134	134	134	134
135	135	135	135	135	135	135	135	135	135	135
136	136	136	136	136	136	136	136	136	136	136
137	137	137	137	137	137	137	137	137	138	138
138	138	138	138	138	138	138	138	139	139	139
139	139	139	139	139	139	139	140	140	140	140
140	140	140	140	140	140	141	141	141	141	141
141	141	141	141	141	141	142	142	142	142	142
142	142	142	142	142	143	143	143	143	143	143
143	143	143	143	143	144	144	144	144	144	144
144	144	144	144	145	145	145	145	145	145	145
145	145	145	145	146	146	146	146	146	146	146
146	146	146	146	147	147	147	147	147	147	148
147	147	147	147	148	148	148	148	148	149	149
148	148	148	149	149	149	149	149	149	150	150
149	149	149	150	150	150	150	150	150	151	151
150	150	150	151	151	151	151	151	152	152	152
151	151	151	152	152	152	152	152	153	153	153
152	152	152	153	153	153	153	154	154	154	154
153	153	153	154	154	154	154	155	155	155	155
154	154	154	155	155	155	155	156	156	156	156
155	155	155	156	156	156	156	157	157	157	158
156	156	156	157	157	157	158	158	158	158	159
157	157	158	158	158	158	159	159	159	159	160
158	158	159	159	159	159	160	160	160	161	161
159	159	160	160	160	160	161	161	161	162	162
160	160	161	161	161	161	162	162	162	163	163

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

3 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.4

DD	PERCENT of + 3/4 MATERIAL									
	11	12	13	14	15	16	17	18	19	20
80	74	73	72	72	71	70	69	69	68	67
81	75	74	73	73	72	71	71	70	69	68
82	76	75	75	74	73	73	72	71	70	70
83	77	76	76	75	74	74	73	72	72	71
84	78	77	77	76	76	75	74	74	73	72
85	79	79	78	77	77	76	75	75	74	73
86	80	80	79	79	78	77	77	76	75	75
87	81	81	80	80	79	78	78	77	76	76
88	83	82	81	81	80	80	79	78	78	77
89	84	83	83	82	81	81	80	80	79	78
90	85	84	84	83	83	82	81	81	80	80
91	86	85	85	84	84	83	83	82	81	81
92	87	87	86	86	85	84	84	83	83	82
93	88	88	87	87	86	86	85	84	84	83
94	89	89	88	88	87	87	86	86	85	85
95	90	90	90	89	89	88	87	87	86	86
96	92	91	91	90	90	89	89	88	88	87
97	93	92	92	91	91	90	90	89	89	88
98	94	93	93	92	92	92	91	91	90	90
99	95	95	94	94	93	93	92	92	91	91
100	96	96	95	95	94	94	93	93	93	92
101	97	97	96	96	96	95	95	94	94	93
102	98	98	98	97	97	96	96	95	95	95
103	99	99	99	98	98	98	97	97	96	96
104	101	100	100	99	99	99	98	98	97	97
105	102	101	101	101	100	100	100	99	99	98
106	103	102	102	102	101	101	101	100	100	100
107	104	104	103	103	103	102	102	102	101	101
108	105	105	104	104	104	103	103	103	102	102
109	106	106	106	105	105	105	104	104	104	103
110	107	107	107	106	106	106	106	105	105	105
111	108	108	108	108	107	107	107	106	106	106
112	110	109	109	109	109	108	108	108	107	107
113	111	110	110	110	110	109	109	109	109	108
114	112	112	111	111	111	111	110	110	110	110
115	113	113	112	112	112	112	112	111	111	111
116	114	114	114	113	113	113	113	113	112	112
117	115	115	115	115	114	114	114	114	114	113
118	116	116	116	116	116	115	115	115	115	115
119	117	117	117	117	117	117	116	116	116	116
120	119	118	118	118	118	118	118	117	117	117

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

4 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.4

DD	PERCENT of + 3/4 MATERIAL									
	11	12	13	14	15	16	17	18	19	20
121	120	120	119	119	119	119	119	119	118	118
122	121	121	121	120	120	120	120	120	120	120
123	122	122	122	122	121	121	121	121	121	121
124	123	123	123	123	123	123	122	122	122	122
125	124	124	124	124	124	124	124	124	123	123
126	125	125	125	125	125	125	125	125	125	125
127	126	126	126	126	126	126	126	126	126	126
128	128	127	127	127	127	127	127	127	127	127
129	129	129	129	129	129	128	128	128	128	128
130	130	130	130	130	130	130	130	130	130	130
131	131	131	131	131	131	131	131	131	131	131
132	132	132	132	132	132	132	132	132	132	132
133	133	133	133	133	133	133	133	133	133	133
134	134	134	134	134	134	134	134	134	135	135
135	135	135	135	136	136	136	136	136	136	136
136	137	137	137	137	137	137	137	137	137	137
137	138	138	138	138	138	138	138	138	138	138
138	139	139	139	139	139	139	139	139	139	140
139	140	140	140	140	140	140	140	141	141	141
140	141	141	141	141	141	142	142	142	142	142
141	142	142	142	142	143	143	143	143	143	143
142	143	143	144	144	144	144	144	144	144	145
143	144	145	145	145	145	145	145	145	146	146
144	146	146	146	146	146	146	147	147	147	147
145	147	147	147	147	147	148	148	148	148	148
146	148	148	148	148	149	149	149	149	149	150
147	149	149	149	149	150	150	150	150	151	151
148	150	150	150	151	151	151	151	152	152	152
149	151	151	152	152	152	152	153	153	153	153
150	152	152	153	153	153	153	154	154	154	155
151	153	154	154	154	154	155	155	155	156	156
152	154	155	155	155	156	156	156	156	157	157
153	156	156	156	156	157	157	157	158	158	158
154	157	157	157	158	158	158	159	159	159	160
155	158	158	158	159	159	159	160	160	160	161
156	159	159	160	160	160	161	161	161	162	162
157	160	160	161	161	161	162	162	163	163	163
158	161	162	162	162	163	163	163	164	164	165
159	162	163	163	163	164	164	165	165	165	166
160	163	164	164	165	165	165	166	166	167	167

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

5 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.4

DD	PERCENT of + 3/4 MATERIAL									
	21	22	23	24	25	26	27	28	29	30
80	66	65	65	64	63	62	61	60	59	58
81	67	67	66	65	64	63	62	61	60	59
82	69	68	67	66	65	65	64	63	62	61
83	70	69	68	68	67	66	65	64	63	62
84	71	71	70	69	68	67	66	65	64	64
85	73	72	71	70	69	69	68	67	66	65
86	74	73	72	72	71	70	69	68	67	66
87	75	74	74	73	72	71	70	70	69	68
88	76	76	75	74	73	73	72	71	70	69
89	78	77	76	75	75	74	73	72	72	71
90	79	78	78	77	76	75	75	74	73	72
91	80	79	79	78	77	77	76	75	74	74
92	81	81	80	79	79	78	77	77	76	75
93	83	82	81	81	80	79	79	78	77	76
94	84	83	83	82	81	81	80	79	79	78
95	85	85	84	83	83	82	81	81	80	79
96	86	86	85	85	84	83	83	82	81	81
97	88	87	87	86	85	85	84	83	83	82
98	89	88	88	87	87	86	86	85	84	84
99	90	90	89	89	88	87	87	86	86	85
100	92	91	91	90	89	89	88	88	87	86
101	93	92	92	91	91	90	90	89	88	88
102	94	94	93	93	92	92	91	90	90	89
103	95	95	94	94	93	93	92	92	91	91
104	97	96	96	95	95	94	94	93	93	92
105	98	97	97	97	96	96	95	95	94	94
106	99	99	98	98	97	97	96	96	95	95
107	100	100	100	99	99	98	98	97	97	96
108	102	101	101	100	100	100	99	99	98	98
109	103	103	102	102	101	101	101	100	100	99
110	104	104	103	103	103	102	102	102	101	101
111	105	105	105	104	104	104	103	103	103	102
112	107	106	106	106	105	105	105	104	104	104
113	108	108	107	107	107	106	106	106	105	105
114	109	109	109	108	108	108	107	107	107	106
115	111	110	110	110	109	109	109	108	108	108
116	112	112	111	111	111	110	110	110	110	109
117	113	113	113	112	112	112	112	111	111	111
118	114	114	114	114	113	113	113	113	112	112
119	116	115	115	115	115	115	114	114	114	114
120	117	117	116	116	116	116	116	115	115	115

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

6 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.4

DD	PERCENT of + 3/4 MATERIAL									
	21	22	23	24	25	26	27	28	29	30
121	118	118	118	118	117	117	117	117	117	116
122	119	119	119	119	119	119	118	118	118	118
123	121	121	120	120	120	120	120	120	119	119
124	122	122	122	122	121	121	121	121	121	121
125	123	123	123	123	123	123	122	122	122	122
126	124	124	124	124	124	124	124	124	124	124
127	126	126	126	125	125	125	125	125	125	125
128	127	127	127	127	127	127	127	127	126	126
129	128	128	128	128	128	128	128	128	128	128
130	130	129	129	129	129	129	129	129	129	129
131	131	131	131	131	131	131	131	131	131	131
132	132	132	132	132	132	132	132	132	132	132
133	133	133	133	133	133	133	133	133	133	134
134	135	135	135	135	135	135	135	135	135	135
135	136	136	136	136	136	136	136	136	136	136
136	137	137	137	137	137	137	138	138	138	138
137	138	138	139	139	139	139	139	139	139	139
138	140	140	140	140	140	140	140	140	141	141
139	141	141	141	141	141	142	142	142	142	142
140	142	142	142	143	143	143	143	143	143	144
141	143	144	144	144	144	144	144	145	145	145
142	145	145	145	145	145	146	146	146	146	146
143	146	146	146	147	147	147	147	147	148	148
144	147	147	148	148	148	148	149	149	149	149
145	149	149	149	149	149	150	150	150	150	151
146	150	150	150	150	151	151	151	152	152	152
147	151	151	152	152	152	152	153	153	153	154
148	152	153	153	153	153	154	154	154	155	155
149	154	154	154	154	155	155	155	156	156	156
150	155	155	155	156	156	156	157	157	157	158
151	156	156	157	157	157	158	158	158	159	159
152	157	158	158	158	159	159	159	160	160	161
153	159	159	159	160	160	160	161	161	162	162
154	160	160	161	161	161	162	162	163	163	164
155	161	162	162	162	163	163	164	164	164	165
156	162	163	163	164	164	165	165	165	166	166
157	164	164	165	165	165	166	166	167	167	168
158	165	165	166	166	167	167	168	168	169	169
159	166	167	167	168	168	169	169	170	170	171
160	167	168	168	169	169	170	170	171	172	172

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

7 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.4

DD	PERCENT of + 3/4 MATERIAL									
	31	32	33	34	35	36	37	38	39	40
80	57	56	54	53	52	51	50	48	47	45
81	58	57	56	55	54	52	51	50	49	47
82	60	59	57	56	55	54	53	51	50	49
83	61	60	59	58	57	56	54	53	52	50
84	63	62	60	59	58	57	56	55	53	52
85	64	63	62	61	60	59	58	56	55	54
86	65	64	63	62	61	60	59	58	57	55
87	67	66	65	64	63	62	61	60	58	57
88	68	67	66	65	64	63	62	61	60	59
89	70	69	68	67	66	65	64	63	62	60
90	71	70	69	68	67	66	65	64	63	62
91	73	72	71	70	69	68	67	66	65	64
92	74	73	72	72	71	70	69	68	67	65
93	76	75	74	73	72	71	70	69	68	67
94	77	76	75	75	74	73	72	71	70	69
95	78	78	77	76	75	74	73	72	71	70
96	80	79	78	78	77	76	75	74	73	72
97	81	81	80	79	78	77	77	76	75	74
98	83	82	81	81	80	79	78	77	76	75
99	84	84	83	82	81	81	80	79	78	77
100	86	85	84	84	83	82	81	81	80	79
101	87	87	86	85	84	84	83	82	81	80
102	89	88	87	87	86	85	85	84	83	82
103	90	89	89	88	87	87	86	85	85	84
104	92	91	90	90	89	88	88	87	86	85
105	93	92	92	91	91	90	89	89	88	87
106	94	94	93	93	92	91	91	90	90	89
107	96	95	95	94	94	93	92	92	91	90
108	97	97	96	96	95	95	94	93	93	92
109	99	98	98	97	97	96	96	95	94	94
110	100	100	99	99	98	98	97	97	96	95
111	102	101	101	100	100	99	99	98	98	97
112	103	103	102	102	101	101	100	100	99	99
113	105	104	104	103	103	102	102	101	101	100
114	106	106	105	105	104	104	104	103	103	102
115	107	107	107	106	106	106	105	105	104	104
116	109	109	108	108	107	107	107	106	106	105
117	110	110	110	109	109	109	108	108	108	107
118	112	112	111	111	111	110	110	110	109	109
119	113	113	113	112	112	112	111	111	111	110
120	115	114	114	114	114	113	113	113	112	112

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

8 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.4

DD	PERCENT of + 3/4 MATERIAL									
	31	32	33	34	35	36	37	38	39	40
121	116	116	116	115	115	115	115	114	114	114
122	118	117	117	117	117	116	116	116	116	115
123	119	119	119	118	118	118	118	118	117	117
124	121	120	120	120	120	120	119	119	119	119
125	122	122	122	122	121	121	121	121	121	120
126	123	123	123	123	123	123	123	122	122	122
127	125	125	125	125	124	124	124	124	124	124
128	126	126	126	126	126	126	126	126	126	125
129	128	128	128	128	127	127	127	127	127	127
130	129	129	129	129	129	129	129	129	129	129
131	131	131	131	131	131	131	131	131	130	130
132	132	132	132	132	132	132	132	132	132	132
133	134	134	134	134	134	134	134	134	134	134
134	135	135	135	135	135	135	135	135	135	135
135	136	137	137	137	137	137	137	137	137	137
136	138	138	138	138	138	138	138	139	139	139
137	139	139	140	140	140	140	140	140	140	140
138	141	141	141	141	141	141	142	142	142	142
139	142	142	143	143	143	143	143	143	144	144
140	144	144	144	144	144	145	145	145	145	145
141	145	145	146	146	146	146	146	147	147	147
142	147	147	147	147	147	148	148	148	149	149
143	148	148	149	149	149	149	150	150	150	150
144	149	150	150	150	151	151	151	151	152	152
145	151	151	152	152	152	152	153	153	153	154
146	152	153	153	153	154	154	154	155	155	155
147	154	154	154	155	155	156	156	156	157	157
148	155	156	156	156	157	157	158	158	158	159
149	157	157	157	158	158	159	159	160	160	160
150	158	159	159	159	160	160	161	161	162	162
151	160	160	160	161	161	162	162	163	163	164
152	161	162	162	162	163	163	164	164	165	165
153	163	163	163	164	164	165	165	166	167	167
154	164	164	165	165	166	166	167	168	168	169
155	165	166	166	167	167	168	169	169	170	170
156	167	167	168	168	169	170	170	171	171	172
157	168	169	169	170	171	171	172	172	173	174
158	170	170	171	172	172	173	173	174	175	175
159	171	172	172	173	174	174	175	176	176	177
160	173	173	174	175	175	176	177	177	178	179

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

9 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.5

DD	PERCENT of + 3/4 MATERIAL									
	1	2	3	4	5	6	7	8	9	10
80	79	79	78	78	77	76	76	75	74	74
81	80	80	79	79	78	77	77	76	75	75
82	81	81	80	80	79	78	78	77	77	76
83	82	82	81	81	80	80	79	78	78	77
84	83	83	82	82	81	81	80	79	79	78
85	84	84	83	83	82	82	81	80	80	79
86	85	85	84	84	83	83	82	82	81	80
87	86	86	85	85	84	84	83	83	82	81
88	88	87	86	86	85	85	84	84	83	83
89	89	88	88	87	86	86	85	85	84	84
90	90	89	89	88	88	87	86	86	85	85
91	91	90	90	89	89	88	88	87	86	86
92	92	91	91	90	90	89	89	88	88	87
93	93	92	92	91	91	90	90	89	89	88
94	94	93	93	92	92	91	91	90	90	89
95	95	94	94	93	93	92	92	91	91	90
96	96	95	95	94	94	93	93	92	92	91
97	97	96	96	95	95	94	94	93	93	93
98	98	97	97	96	96	95	95	95	94	94
99	99	98	98	97	97	97	96	96	95	95
100	100	99	99	98	98	98	97	97	96	96
101	101	100	100	99	99	99	98	98	97	97
102	102	101	101	101	100	100	99	99	99	98
103	103	102	102	102	101	101	100	100	100	99
104	104	103	103	103	102	102	101	101	101	100
105	105	104	104	104	103	103	103	102	102	101
106	106	105	105	105	104	104	104	103	103	103
107	107	106	106	106	105	105	105	104	104	104
108	108	107	107	107	106	106	106	105	105	105
109	109	108	108	108	108	107	107	107	106	106
110	110	109	109	109	109	108	108	108	107	107
111	111	110	110	110	110	109	109	109	108	108
112	112	111	111	111	111	110	110	110	109	109
113	113	113	112	112	112	111	111	111	111	110
114	114	114	113	113	113	113	112	112	112	111
115	115	115	114	114	114	114	113	113	113	113
116	116	116	115	115	115	115	114	114	114	114
117	117	117	116	116	116	116	115	115	115	115
118	118	118	117	117	117	117	117	116	116	116
119	119	119	118	118	118	118	118	117	117	117
120	120	120	119	119	119	119	119	118	118	118

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

10 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.5

DD	PERCENT of + 3/4 MATERIAL									
	1	2	3	4	5	6	7	8	9	10
121	121	121	120	120	120	120	120	120	119	119
122	122	122	122	121	121	121	121	121	120	120
123	123	123	123	122	122	122	122	122	122	121
124	124	124	124	123	123	123	123	123	123	123
125	125	125	125	124	124	124	124	124	124	124
126	126	126	126	126	125	125	125	125	125	125
127	127	127	127	127	126	126	126	126	126	126
128	128	128	128	128	128	127	127	127	127	127
129	129	129	129	129	129	128	128	128	128	128
130	130	130	130	130	130	130	129	129	129	129
131	131	131	131	131	131	131	131	130	130	130
132	132	132	132	132	132	132	132	132	131	131
133	133	133	133	133	133	133	133	133	133	133
134	134	134	134	134	134	134	134	134	134	134
135	135	135	135	135	135	135	135	135	135	135
136	136	136	136	136	136	136	136	136	136	136
137	137	137	137	137	137	137	137	137	137	137
138	138	138	138	138	138	138	138	138	138	138
139	139	139	139	139	139	139	139	139	139	139
140	140	140	140	140	140	140	140	140	140	140
141	141	141	141	141	141	141	141	141	141	141
142	142	142	142	142	142	142	142	142	142	143
143	143	143	143	143	143	143	143	143	144	144
144	144	144	144	144	144	144	145	145	145	145
145	145	145	145	145	145	145	146	146	146	146
146	146	146	146	146	146	147	147	147	147	147
147	147	147	147	147	148	148	148	148	148	148
148	148	148	148	148	149	149	149	149	149	149
149	149	149	149	149	150	150	150	150	150	150
150	150	150	150	151	151	151	151	151	151	151
151	151	151	151	152	152	152	152	152	152	153
152	152	152	152	153	153	153	153	153	153	154
153	153	153	153	154	154	154	154	154	155	155
154	154	154	155	155	155	155	155	155	156	156
155	155	155	156	156	156	156	156	157	157	157
156	156	156	157	157	157	157	157	158	158	158
157	157	157	158	158	158	158	158	159	159	159
158	158	158	159	159	159	159	160	160	160	160
159	159	159	160	160	160	160	161	161	161	161
160	160	160	161	161	161	161	162	162	162	163

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

11 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.5

DD	PERCENT of + 3/4 MATERIAL									
	11	12	13	14	15	16	17	18	19	20
80	73	72	71	71	70	69	68	67	67	66
81	74	73	73	72	71	70	69	69	68	67
82	75	74	74	73	72	71	71	70	69	68
83	76	76	75	74	73	73	72	71	70	69
84	77	77	76	75	75	74	73	72	72	71
85	79	78	77	76	76	75	74	74	73	72
86	80	79	78	78	77	76	75	75	74	73
87	81	80	79	79	78	77	77	76	75	74
88	82	81	81	80	79	79	78	77	76	76
89	83	82	82	81	80	80	79	78	78	77
90	84	84	83	82	82	81	80	80	79	78
91	85	85	84	83	83	82	82	81	80	79
92	86	86	85	85	84	83	83	82	81	81
93	88	87	86	86	85	85	84	83	83	82
94	89	88	88	87	86	86	85	84	84	83
95	90	89	89	88	88	87	86	86	85	84
96	91	90	90	89	89	88	88	87	86	86
97	92	92	91	90	90	89	89	88	88	87
98	93	93	92	92	91	91	90	89	89	88
99	94	94	93	93	92	92	91	91	90	89
100	95	95	94	94	93	93	92	92	91	91
101	97	96	96	95	95	94	94	93	92	92
102	98	97	97	96	96	95	95	94	94	93
103	99	98	98	97	97	96	96	95	95	94
104	100	99	99	99	98	98	97	97	96	96
105	101	101	100	100	99	99	98	98	97	97
106	102	102	101	101	100	100	100	99	99	98
107	103	103	102	102	102	101	101	100	100	99
108	104	104	104	103	103	102	102	102	101	101
109	106	105	105	104	104	104	103	103	102	102
110	107	106	106	106	105	105	104	104	104	103
111	108	107	107	107	106	106	106	105	105	104
112	109	109	108	108	108	107	107	106	106	106
113	110	110	109	109	109	108	108	108	107	107
114	111	111	111	110	110	110	109	109	109	108
115	112	112	112	111	111	111	110	110	110	109
116	113	113	113	113	112	112	112	111	111	111
117	114	114	114	114	113	113	113	113	112	112
118	116	115	115	115	115	114	114	114	113	113
119	117	117	116	116	116	116	115	115	115	114
120	118	118	117	117	117	117	117	116	116	116

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

12 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.5

DD	PERCENT of + 3/4 MATERIAL									
	11	12	13	14	15	16	17	18	19	20
121	119	119	119	118	118	118	118	117	117	117
122	120	120	120	120	119	119	119	119	118	118
123	121	121	121	121	120	120	120	120	120	119
124	122	122	122	122	122	121	121	121	121	121
125	123	123	123	123	123	123	122	122	122	122
126	125	124	124	124	124	124	124	124	123	123
127	126	126	125	125	125	125	125	125	125	124
128	127	127	127	126	126	126	126	126	126	126
129	128	128	128	128	128	127	127	127	127	127
130	129	129	129	129	129	129	129	128	128	128
131	130	130	130	130	130	130	130	130	130	129
132	131	131	131	131	131	131	131	131	131	131
133	132	132	132	132	132	132	132	132	132	132
134	134	134	134	133	133	133	133	133	133	133
135	135	135	135	135	135	135	135	134	134	134
136	136	136	136	136	136	136	136	136	136	136
137	137	137	137	137	137	137	137	137	137	137
138	138	138	138	138	138	138	138	138	138	138
139	139	139	139	139	139	139	139	139	139	139
140	140	140	140	140	140	141	141	141	141	141
141	141	142	142	142	142	142	142	142	142	142
142	143	143	143	143	143	143	143	143	143	143
143	144	144	144	144	144	144	144	144	144	144
144	145	145	145	145	145	145	145	145	146	146
145	146	146	146	146	146	146	147	147	147	147
146	147	147	147	147	148	148	148	148	148	148
147	148	148	148	149	149	149	149	149	149	149
148	149	149	150	150	150	150	150	150	151	151
149	150	151	151	151	151	151	151	152	152	152
150	152	152	152	152	152	152	153	153	153	153
151	153	153	153	153	153	154	154	154	154	154
152	154	154	154	154	155	155	155	155	155	156
153	155	155	155	156	156	156	156	156	157	157
154	156	156	156	157	157	157	157	158	158	158
155	157	157	158	158	158	158	159	159	159	159
156	158	159	159	159	159	160	160	160	160	161
157	159	160	160	160	160	161	161	161	162	162
158	161	161	161	161	162	162	162	163	163	163
159	162	162	162	163	163	163	163	164	164	164
160	163	163	163	164	164	164	165	165	165	166

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

13 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.5

DD	PERCENT of + 3/4 MATERIAL									
	21	22	23	24	25	26	27	28	29	30
80	65	64	63	62	61	60	59	58	57	55
81	66	65	64	63	62	61	60	59	58	57
82	67	66	65	65	64	63	62	61	59	58
83	69	68	67	66	65	64	63	62	61	60
84	70	69	68	67	66	65	64	63	62	61
85	71	70	69	68	68	67	66	65	64	63
86	72	72	71	70	69	68	67	66	65	64
87	74	73	72	71	70	69	68	67	66	65
88	75	74	73	72	72	71	70	69	68	67
89	76	75	75	74	73	72	71	70	69	68
90	77	77	76	75	74	73	73	72	71	70
91	79	78	77	76	76	75	74	73	72	71
92	80	79	78	78	77	76	75	74	74	73
93	81	81	80	79	78	77	77	76	75	74
94	82	82	81	80	80	79	78	77	76	75
95	84	83	82	82	81	80	79	79	78	77
96	85	84	84	83	82	81	81	80	79	78
97	86	86	85	84	84	83	82	81	81	80
98	88	87	86	86	85	84	83	83	82	81
99	89	88	88	87	86	86	85	84	83	83
100	90	89	89	88	88	87	86	86	85	84
101	91	91	90	90	89	88	88	87	86	85
102	93	92	91	91	90	90	89	88	88	87
103	94	93	93	92	92	91	90	90	89	88
104	95	95	94	93	93	92	92	91	90	90
105	96	96	95	95	94	94	93	92	92	91
106	98	97	97	96	96	95	94	94	93	93
107	99	98	98	97	97	96	96	95	95	94
108	100	100	99	99	98	98	97	97	96	95
109	101	101	101	100	100	99	99	98	97	97
110	103	102	102	101	101	100	100	99	99	98
111	104	104	103	103	102	102	101	101	100	100
112	105	105	104	104	104	103	103	102	102	101
113	107	106	106	105	105	104	104	104	103	103
114	108	107	107	107	106	106	105	105	104	104
115	109	109	108	108	108	107	107	106	106	105
116	110	110	110	109	109	109	108	108	107	107
117	112	111	111	111	110	110	109	109	109	108
118	113	113	112	112	112	111	111	111	110	110
119	114	114	114	113	113	113	112	112	112	111
120	115	115	115	115	114	114	114	113	113	113

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

14 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.5

DD	PERCENT of + 3/4 MATERIAL									
	21	22	23	24	25	26	27	28	29	30
121	117	116	116	116	116	115	115	115	114	114
122	118	118	117	117	117	117	116	116	116	115
123	119	119	119	118	118	118	118	117	117	117
124	120	120	120	120	120	119	119	119	119	118
125	122	122	121	121	121	121	120	120	120	120
126	123	123	123	122	122	122	122	122	121	121
127	124	124	124	124	124	123	123	123	123	123
128	126	125	125	125	125	125	125	124	124	124
129	127	127	127	126	126	126	126	126	126	125
130	128	128	128	128	128	127	127	127	127	127
131	129	129	129	129	129	129	129	129	128	128
132	131	131	130	130	130	130	130	130	130	130
133	132	132	132	132	132	131	131	131	131	131
134	133	133	133	133	133	133	133	133	133	133
135	134	134	134	134	134	134	134	134	134	134
136	136	136	136	136	136	136	136	136	135	135
137	137	137	137	137	137	137	137	137	137	137
138	138	138	138	138	138	138	138	138	138	138
139	139	139	140	140	140	140	140	140	140	140
140	141	141	141	141	141	141	141	141	141	141
141	142	142	142	142	142	142	142	142	143	143
142	143	143	143	143	144	144	144	144	144	144
143	145	145	145	145	145	145	145	145	145	145
144	146	146	146	146	146	146	146	147	147	147
145	147	147	147	147	148	148	148	148	148	148
146	148	148	149	149	149	149	149	149	150	150
147	150	150	150	150	150	150	151	151	151	151
148	151	151	151	151	152	152	152	152	152	153
149	152	152	153	153	153	153	153	154	154	154
150	153	154	154	154	154	154	155	155	155	155
151	155	155	155	155	156	156	156	156	157	157
152	156	156	156	157	157	157	157	158	158	158
153	157	157	158	158	158	159	159	159	159	160
154	158	159	159	159	160	160	160	161	161	161
155	160	160	160	161	161	161	162	162	162	163
156	161	161	162	162	162	163	163	163	164	164
157	162	163	163	163	164	164	164	165	165	165
158	164	164	164	165	165	165	166	166	166	167
159	165	165	165	166	166	167	167	167	168	168
160	166	166	167	167	168	168	168	169	169	170

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

15 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.5

DD	PERCENT of + 3/4 MATERIAL									
	31	32	33	34	35	36	37	38	39	40
80	54	53	52	50	49	48	46	45	43	42
81	56	55	53	52	51	49	48	47	45	43
82	57	56	55	54	52	51	50	48	47	45
83	59	57	56	55	54	52	51	50	48	47
84	60	59	58	57	55	54	53	51	50	48
85	62	60	59	58	57	56	54	53	52	50
86	63	62	61	60	58	57	56	55	53	52
87	64	63	62	61	60	59	57	56	55	53
88	66	65	64	63	61	60	59	58	56	55
89	67	66	65	64	63	62	61	59	58	57
90	69	68	67	66	65	63	62	61	60	58
91	70	69	68	67	66	65	64	63	61	60
92	72	71	70	69	68	67	65	64	63	62
93	73	72	71	70	69	68	67	66	65	63
94	75	74	73	72	71	70	69	67	66	65
95	76	75	74	73	72	71	70	69	68	67
96	77	77	76	75	74	73	72	71	70	68
97	79	78	77	76	75	74	73	72	71	70
98	80	80	79	78	77	76	75	74	73	72
99	82	81	80	79	78	77	77	76	75	73
100	83	82	82	81	80	79	78	77	76	75
101	85	84	83	82	81	81	80	79	78	77
102	86	85	85	84	83	82	81	80	79	78
103	88	87	86	85	85	84	83	82	81	80
104	89	88	88	87	86	85	84	84	83	82
105	90	90	89	88	88	87	86	85	84	83
106	92	91	91	90	89	88	88	87	86	85
107	93	93	92	91	91	90	89	88	88	87
108	95	94	94	93	92	92	91	90	89	88
109	96	96	95	94	94	93	92	92	91	90
110	98	97	97	96	95	95	94	93	93	92
111	99	99	98	97	97	96	96	95	94	93
112	101	100	100	99	98	98	97	97	96	95
113	102	102	101	100	100	99	99	98	97	97
114	104	103	103	102	101	101	100	100	99	98
115	105	105	104	104	103	102	102	101	101	100
116	106	106	106	105	105	104	104	103	102	102
117	108	107	107	107	106	106	105	105	104	103
118	109	109	109	108	108	107	107	106	106	105
119	111	110	110	110	109	109	108	108	107	107
120	112	112	111	111	111	110	110	109	109	108

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

16 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.5

DD	PERCENT of + 3/4 MATERIAL									
	31	32	33	34	35	36	37	38	39	40
121	114	113	113	113	112	112	111	111	111	110
122	115	115	114	114	114	113	113	113	112	112
123	117	116	116	116	115	115	115	114	114	113
124	118	118	117	117	117	117	116	116	116	115
125	119	119	119	119	118	118	118	117	117	117
126	121	121	120	120	120	120	119	119	119	118
127	122	122	122	122	121	121	121	121	120	120
128	124	124	123	123	123	123	123	122	122	122
129	125	125	125	125	125	124	124	124	124	123
130	127	127	126	126	126	126	126	126	125	125
131	128	128	128	128	128	127	127	127	127	127
132	130	130	129	129	129	129	129	129	129	128
133	131	131	131	131	131	131	130	130	130	130
134	133	132	132	132	132	132	132	132	132	132
135	134	134	134	134	134	134	134	134	134	133
136	135	135	135	135	135	135	135	135	135	135
137	137	137	137	137	137	137	137	137	137	137
138	138	138	138	138	138	138	138	138	138	138
139	140	140	140	140	140	140	140	140	140	140
140	141	141	141	141	141	142	142	142	142	142
141	143	143	143	143	143	143	143	143	143	143
142	144	144	144	144	145	145	145	145	145	145
143	146	146	146	146	146	146	146	147	147	147
144	147	147	147	147	148	148	148	148	148	148
145	148	149	149	149	149	149	150	150	150	150
146	150	150	150	150	151	151	151	151	152	152
147	151	152	152	152	152	152	153	153	153	153
148	153	153	153	154	154	154	154	155	155	155
149	154	155	155	155	155	156	156	156	156	157
150	156	156	156	157	157	157	157	158	158	158
151	157	157	158	158	158	159	159	159	160	160
152	159	159	159	160	160	160	161	161	161	162
153	160	160	161	161	161	162	162	163	163	163
154	162	162	162	163	163	163	164	164	165	165
155	163	163	164	164	165	165	165	166	166	167
156	164	165	165	166	166	167	167	167	168	168
157	166	166	167	167	168	168	169	169	170	170
158	167	168	168	169	169	170	170	171	171	172
159	169	169	170	170	171	171	172	172	173	173
160	170	171	171	172	172	173	173	174	175	175

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

17 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.6

DD	PERCENT of + 3/4 MATERIAL									
	1	2	3	4	5	6	7	8	9	10
80	79	79	78	77	77	76	75	75	74	73
81	80	80	79	78	78	77	76	76	75	74
82	81	81	80	79	79	78	77	77	76	75
83	82	82	81	81	80	79	79	78	77	76
84	83	83	82	82	81	80	80	79	78	77
85	84	84	83	83	82	81	81	80	79	79
86	85	85	84	84	83	82	82	81	80	80
87	86	86	85	85	84	83	83	82	81	81
88	87	87	86	86	85	85	84	83	83	82
89	88	88	87	87	86	86	85	84	84	83
90	89	89	88	88	87	87	86	85	85	84
91	90	90	89	89	88	88	87	86	86	85
92	91	91	90	90	89	89	88	88	87	86
93	92	92	91	91	90	90	89	89	88	87
94	94	93	92	92	91	91	90	90	89	89
95	95	94	94	93	92	92	91	91	90	90
96	96	95	95	94	94	93	92	92	91	91
97	97	96	96	95	95	94	94	93	92	92
98	98	97	97	96	96	95	95	94	94	93
99	99	98	98	97	97	96	96	95	95	94
100	100	99	99	98	98	97	97	96	96	95
101	101	100	100	99	99	98	98	97	97	96
102	102	101	101	100	100	99	99	98	98	97
103	103	102	102	101	101	100	100	100	99	99
104	104	103	103	102	102	102	101	101	100	100
105	105	104	104	103	103	103	102	102	101	101
106	106	105	105	104	104	104	103	103	102	102
107	107	106	106	106	105	105	104	104	103	103
108	108	107	107	107	106	106	105	105	105	104
109	109	108	108	108	107	107	106	106	106	105
110	110	109	109	109	108	108	108	107	107	106
111	111	110	110	110	109	109	109	108	108	107
112	112	111	111	111	110	110	110	109	109	109
113	113	112	112	112	111	111	111	110	110	110
114	114	113	113	113	112	112	112	111	111	111
115	115	114	114	114	114	113	113	113	112	112
116	116	115	115	115	115	114	114	114	113	113
117	117	116	116	116	116	115	115	115	114	114
118	118	117	117	117	117	116	116	116	116	115
119	119	119	118	118	118	117	117	117	117	116
120	120	120	119	119	119	119	118	118	118	117

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF											2.6
DD	1	2	3	4	5	6	7	8	9	10	
121	121	121	120	120	120	120	119	119	119	119	
122	122	122	121	121	121	121	120	120	120	120	
123	123	123	122	122	122	122	122	121	121	121	
124	124	124	123	123	123	123	123	122	122	122	
125	125	125	124	124	124	124	124	123	123	123	
126	126	126	125	125	125	125	125	125	124	124	
127	127	127	127	126	126	126	126	126	125	125	
128	128	128	128	127	127	127	127	127	127	126	
129	129	129	129	128	128	128	128	128	128	127	
130	130	130	130	129	129	129	129	129	129	129	
131	131	131	131	131	130	130	130	130	130	130	
132	132	132	132	132	131	131	131	131	131	131	
133	133	133	133	133	132	132	132	132	132	132	
134	134	134	134	134	134	133	133	133	133	133	
135	135	135	135	135	135	135	134	134	134	134	
136	136	136	136	136	136	136	135	135	135	135	
137	137	137	137	137	137	137	137	136	136	136	
138	138	138	138	138	138	138	138	138	138	137	
139	139	139	139	139	139	139	139	139	139	139	
140	140	140	140	140	140	140	140	140	140	140	
141	141	141	141	141	141	141	141	141	141	141	
142	142	142	142	142	142	142	142	142	142	142	
143	143	143	143	143	143	143	143	143	143	143	
144	144	144	144	144	144	144	144	144	144	144	
145	145	145	145	145	145	145	145	145	145	145	
146	146	146	146	146	146	146	146	146	146	146	
147	147	147	147	147	147	147	147	147	147	147	
148	148	148	148	148	148	148	148	148	149	149	
149	149	149	149	149	149	149	149	150	150	150	
150	150	150	150	150	150	150	151	151	151	151	
151	151	151	151	151	151	152	152	152	152	152	
152	152	152	152	152	152	153	153	153	153	153	
153	153	153	153	153	154	154	154	154	154	154	
154	154	154	154	154	155	155	155	155	155	155	
155	155	155	155	156	156	156	156	156	156	156	
156	156	156	156	157	157	157	157	157	157	157	
157	157	157	157	158	158	158	158	158	158	159	
158	158	158	158	159	159	159	159	159	160	160	
159	159	159	160	160	160	160	160	160	161	161	
160	160	160	161	161	161	161	161	161	162	162	

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

19 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.6

DD	PERCENT of + 3/4 MATERIAL									
	11	12	13	14	15	16	17	18	19	20
80	72	71	71	70	69	68	67	66	65	64
81	73	73	72	71	70	69	68	67	67	66
82	74	74	73	72	71	70	70	69	68	67
83	76	75	74	73	72	72	71	70	69	68
84	77	76	75	74	74	73	72	71	70	69
85	78	77	76	76	75	74	73	72	71	71
86	79	78	78	77	76	75	74	74	73	72
87	80	79	79	78	77	76	76	75	74	73
88	81	81	80	79	78	78	77	76	75	74
89	82	82	81	80	80	79	78	77	76	76
90	83	83	82	81	81	80	79	78	78	77
91	85	84	83	83	82	81	80	80	79	78
92	86	85	84	84	83	82	82	81	80	79
93	87	86	86	85	84	84	83	82	81	81
94	88	87	87	86	85	85	84	83	83	82
95	89	88	88	87	87	86	85	85	84	83
96	90	90	89	88	88	87	86	86	85	84
97	91	91	90	90	89	88	88	87	86	86
98	92	92	91	91	90	89	89	88	87	87
99	94	93	92	92	91	91	90	89	89	88
100	95	94	94	93	92	92	91	91	90	89
101	96	95	95	94	94	93	92	92	91	91
102	97	96	96	95	95	94	94	93	92	92
103	98	98	97	97	96	95	95	94	94	93
104	99	99	98	98	97	97	96	95	95	94
105	100	100	99	99	98	98	97	97	96	96
106	101	101	101	100	100	99	98	98	97	97
107	103	102	102	101	101	100	100	99	99	98
108	104	103	103	102	102	101	101	100	100	99
109	105	104	104	104	103	103	102	102	101	101
110	106	106	105	105	104	104	103	103	102	102
111	107	107	106	106	105	105	104	104	104	103
112	108	108	107	107	107	106	106	105	105	104
113	109	109	109	108	108	107	107	106	106	106
114	110	110	110	109	109	109	108	108	107	107
115	112	111	111	110	110	110	109	109	108	108
116	113	112	112	112	111	111	111	110	110	109
117	114	113	113	113	112	112	112	111	111	111
118	115	115	114	114	114	113	113	113	112	112
119	116	116	115	115	115	114	114	114	113	113
120	117	117	117	116	116	116	115	115	115	114

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

20 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.6

DD	PERCENT of + 3/4 MATERIAL									
	11	12	13	14	15	16	17	18	19	20
121	118	118	118	117	117	117	117	116	116	116
122	119	119	119	119	118	118	118	117	117	117
123	121	120	120	120	120	119	119	119	118	118
124	122	121	121	121	121	120	120	120	120	119
125	123	123	122	122	122	122	121	121	121	121
126	124	124	123	123	123	123	123	122	122	122
127	125	125	125	124	124	124	124	124	123	123
128	126	126	126	126	125	125	125	125	125	124
129	127	127	127	127	127	126	126	126	126	126
130	128	128	128	128	128	128	127	127	127	127
131	130	129	129	129	129	129	129	128	128	128
132	131	131	130	130	130	130	130	130	129	129
133	132	132	132	131	131	131	131	131	131	131
134	133	133	133	133	132	132	132	132	132	132
135	134	134	134	134	134	134	133	133	133	133
136	135	135	135	135	135	135	135	135	134	134
137	136	136	136	136	136	136	136	136	136	136
138	137	137	137	137	137	137	137	137	137	137
139	139	138	138	138	138	138	138	138	138	138
140	140	140	140	140	140	139	139	139	139	139
141	141	141	141	141	141	141	141	141	141	141
142	142	142	142	142	142	142	142	142	142	142
143	143	143	143	143	143	143	143	143	143	143
144	144	144	144	144	144	144	144	144	144	144
145	145	145	145	145	145	145	145	145	146	146
146	146	146	146	147	147	147	147	147	147	147
147	148	148	148	148	148	148	148	148	148	148
148	149	149	149	149	149	149	149	149	149	149
149	150	150	150	150	150	150	150	150	150	151
150	151	151	151	151	151	151	151	152	152	152
151	152	152	152	152	152	153	153	153	153	153
152	153	153	153	154	154	154	154	154	154	154
153	154	154	155	155	155	155	155	155	155	156
154	155	156	156	156	156	156	156	156	157	157
155	157	157	157	157	157	157	158	158	158	158
156	158	158	158	158	158	159	159	159	159	159
157	159	159	159	159	160	160	160	160	160	161
158	160	160	160	160	161	161	161	161	162	162
159	161	161	161	162	162	162	162	163	163	163
160	162	162	163	163	163	163	164	164	164	164

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

21 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.6

DD	PERCENT of + 3/4 MATERIAL									
	21	22	23	24	25	26	27	28	29	30
80	63	62	61	60	59	58	57	56	54	53
81	65	64	63	61	60	59	58	57	56	55
82	66	65	64	63	62	61	60	58	57	56
83	67	66	65	64	63	62	61	60	59	57
84	68	67	66	65	64	63	62	61	60	59
85	70	69	68	67	66	65	64	63	61	60
86	71	70	69	68	67	66	65	64	63	62
87	72	71	70	69	68	67	66	65	64	63
88	73	73	72	71	70	69	68	67	66	65
89	75	74	73	72	71	70	69	68	67	66
90	76	75	74	73	72	71	70	69	68	67
91	77	76	76	75	74	73	72	71	70	69
92	79	78	77	76	75	74	73	72	71	70
93	80	79	78	77	76	76	75	74	73	72
94	81	80	79	79	78	77	76	75	74	73
95	82	82	81	80	79	78	77	76	75	75
96	84	83	82	81	80	80	79	78	77	76
97	85	84	83	83	82	81	80	79	78	77
98	86	85	85	84	83	82	81	81	80	79
99	87	87	86	85	84	84	83	82	81	80
100	89	88	87	86	86	85	84	83	83	82
101	90	89	89	88	87	86	86	85	84	83
102	91	91	90	89	88	88	87	86	85	85
103	92	92	91	90	90	89	88	88	87	86
104	94	93	92	92	91	90	90	89	88	87
105	95	94	94	93	92	92	91	90	90	89
106	96	96	95	94	94	93	92	92	91	90
107	97	97	96	96	95	94	94	93	92	92
108	99	98	98	97	96	96	95	94	94	93
109	100	99	99	98	98	97	97	96	95	95
110	101	101	100	100	99	98	98	97	97	96
111	103	102	102	101	100	100	99	99	98	97
112	104	103	103	102	102	101	101	100	99	99
113	105	105	104	104	103	103	102	101	101	100
114	106	106	105	105	104	104	103	103	102	102
115	108	107	107	106	106	105	105	104	104	103
116	109	108	108	108	107	107	106	106	105	105
117	110	110	109	109	108	108	107	107	106	106
118	111	111	111	110	110	109	109	108	108	107
119	113	112	112	111	111	111	110	110	109	109
120	114	114	113	113	112	112	112	111	111	110

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

22 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.6

DD	PERCENT of + 3/4 MATERIAL									
	21	22	23	24	25	26	27	28	29	30
121	115	115	114	114	114	113	113	113	112	112
122	116	116	116	115	115	115	114	114	114	113
123	118	117	117	117	116	116	116	115	115	115
124	119	119	118	118	118	117	117	117	116	116
125	120	120	120	119	119	119	118	118	118	117
126	122	121	121	121	120	120	120	119	119	119
127	123	123	122	122	122	121	121	121	121	120
128	124	124	124	123	123	123	123	122	122	122
129	125	125	125	125	124	124	124	124	123	123
130	127	126	126	126	126	126	125	125	125	125
131	128	128	127	127	127	127	127	126	126	126
132	129	129	129	129	128	128	128	128	128	127
133	130	130	130	130	130	130	129	129	129	129
134	132	132	131	131	131	131	131	131	130	130
135	133	133	133	133	132	132	132	132	132	132
136	134	134	134	134	134	134	133	133	133	133
137	135	135	135	135	135	135	135	135	135	135
138	137	137	137	136	136	136	136	136	136	136
139	138	138	138	138	138	138	138	138	137	137
140	139	139	139	139	139	139	139	139	139	139
141	141	141	140	140	140	140	140	140	140	140
142	142	142	142	142	142	142	142	142	142	142
143	143	143	143	143	143	143	143	143	143	143
144	144	144	144	144	144	144	144	144	145	145
145	146	146	146	146	146	146	146	146	146	146
146	147	147	147	147	147	147	147	147	147	147
147	148	148	148	148	148	148	149	149	149	149
148	149	149	150	150	150	150	150	150	150	150
149	151	151	151	151	151	151	151	151	152	152
150	152	152	152	152	152	153	153	153	153	153
151	153	153	153	154	154	154	154	154	154	155
152	154	155	155	155	155	155	155	156	156	156
153	156	156	156	156	156	157	157	157	157	157
154	157	157	157	158	158	158	158	158	159	159
155	158	158	159	159	159	159	160	160	160	160
156	160	160	160	160	160	161	161	161	161	162
157	161	161	161	161	162	162	162	163	163	163
158	162	162	163	163	163	163	164	164	164	165
159	163	164	164	164	164	165	165	165	166	166
160	165	165	165	165	166	166	166	167	167	167

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

23 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.6

DD	PERCENT of + 3/4 MATERIAL									
	31	32	33	34	35	36	37	38	39	40
80	52	50	49	48	46	45	43	42	40	38
81	53	52	51	49	48	46	45	43	42	40
82	55	53	52	51	49	48	46	45	43	41
83	56	55	54	52	51	49	48	46	45	43
84	58	56	55	54	52	51	49	48	46	45
85	59	58	57	55	54	53	51	50	48	46
86	60	59	58	57	55	54	53	51	50	48
87	62	61	60	58	57	56	54	53	51	50
88	63	62	61	60	59	57	56	54	53	51
89	65	64	63	61	60	59	57	56	55	53
90	66	65	64	63	62	60	59	58	56	55
91	68	67	66	64	63	62	61	59	58	56
92	69	68	67	66	65	63	62	61	60	58
93	71	70	68	67	66	65	64	62	61	60
94	72	71	70	69	68	67	65	64	63	61
95	74	73	71	70	69	68	67	66	64	63
96	75	74	73	72	71	70	69	67	66	65
97	76	75	74	73	72	71	70	69	68	66
98	78	77	76	75	74	73	72	71	69	68
99	79	78	77	76	75	74	73	72	71	70
100	81	80	79	78	77	76	75	74	73	71
101	82	81	80	79	79	78	76	75	74	73
102	84	83	82	81	80	79	78	77	76	75
103	85	84	83	83	82	81	80	79	78	76
104	87	86	85	84	83	82	81	80	79	78
105	88	87	86	86	85	84	83	82	81	80
106	89	89	88	87	86	85	84	83	82	81
107	91	90	89	89	88	87	86	85	84	83
108	92	92	91	90	89	88	88	87	86	85
109	94	93	92	92	91	90	89	88	87	86
110	95	95	94	93	92	92	91	90	89	88
111	97	96	95	95	94	93	92	92	91	90
112	98	98	97	96	95	95	94	93	92	91
113	100	99	98	98	97	96	96	95	94	93
114	101	100	100	99	99	98	97	96	96	95
115	103	102	101	101	100	99	99	98	97	96
116	104	103	103	102	102	101	100	100	99	98
117	105	105	104	104	103	103	102	101	101	100
118	107	106	106	105	105	104	103	103	102	101
119	108	108	107	107	106	106	105	104	104	103
120	110	109	109	108	108	107	107	106	105	105

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

24 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.6

DD	PERCENT of + 3/4 MATERIAL									
	31	32	33	34	35	36	37	38	39	40
121	111	111	110	110	109	109	108	108	107	106
122	113	112	112	111	111	110	110	109	109	108
123	114	114	113	113	112	112	111	111	110	110
124	116	115	115	114	114	113	113	112	112	111
125	117	117	116	116	115	115	115	114	114	113
126	118	118	118	117	117	117	116	116	115	115
127	120	120	119	119	119	118	118	117	117	116
128	121	121	121	120	120	120	119	119	119	118
129	123	123	122	122	122	121	121	121	120	120
130	124	124	124	123	123	123	122	122	122	121
131	126	125	125	125	125	124	124	124	123	123
132	127	127	127	126	126	126	126	125	125	125
133	129	128	128	128	128	128	127	127	127	126
134	130	130	130	129	129	129	129	129	128	128
135	132	131	131	131	131	131	130	130	130	130
136	133	133	133	133	132	132	132	132	132	131
137	134	134	134	134	134	134	134	133	133	133
138	136	136	136	136	135	135	135	135	135	135
139	137	137	137	137	137	137	137	137	137	136
140	139	139	139	139	139	138	138	138	138	138
141	140	140	140	140	140	140	140	140	140	140
142	142	142	142	142	142	142	142	142	142	141
143	143	143	143	143	143	143	143	143	143	143
144	145	145	145	145	145	145	145	145	145	145
145	146	146	146	146	146	146	146	146	146	146
146	147	148	148	148	148	148	148	148	148	148
147	149	149	149	149	149	149	149	150	150	150
148	150	150	151	151	151	151	151	151	151	151
149	152	152	152	152	152	153	153	153	153	153
150	153	153	154	154	154	154	154	154	155	155
151	155	155	155	155	155	156	156	156	156	156
152	156	156	157	157	157	157	157	158	158	158
153	158	158	158	158	159	159	159	159	160	160
154	159	159	160	160	160	160	161	161	161	161
155	160	161	161	161	162	162	162	162	163	163
156	162	162	163	163	163	163	164	164	164	165
157	163	164	164	164	165	165	165	166	166	166
158	165	165	166	166	166	167	167	167	168	168
159	166	167	167	167	168	168	169	169	169	170
160	168	168	168	169	169	170	170	171	171	171

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

25 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.7

DD	PERCENT of + 3/4 MATERIAL									
	1	2	3	4	5	6	7	8	9	10
80	79	79	78	77	76	76	75	74	73	72
81	80	80	79	78	77	77	76	75	74	74
82	81	81	80	79	79	78	77	76	75	75
83	82	82	81	80	80	79	78	77	77	76
84	83	83	82	81	81	80	79	78	78	77
85	84	84	83	82	82	81	80	79	79	78
86	85	85	84	83	83	82	81	81	80	79
87	86	86	85	84	84	83	82	82	81	80
88	87	87	86	85	85	84	83	83	82	81
89	88	88	87	87	86	85	85	84	83	82
90	89	89	88	88	87	86	86	85	84	84
91	90	90	89	89	88	87	87	86	85	85
92	91	91	90	90	89	88	88	87	86	86
93	92	92	91	91	90	89	89	88	88	87
94	93	93	92	92	91	91	90	89	89	88
95	94	94	93	93	92	92	91	90	90	89
96	95	95	94	94	93	93	92	91	91	90
97	96	96	95	95	94	94	93	93	92	91
98	97	97	96	96	95	95	94	94	93	92
99	99	98	97	97	96	96	95	95	94	94
100	100	99	99	98	97	97	96	96	95	95
101	101	100	100	99	99	98	97	97	96	96
102	102	101	101	100	100	99	99	98	97	97
103	103	102	102	101	101	100	100	99	99	98
104	104	103	103	102	102	101	101	100	100	99
105	105	104	104	103	103	102	102	101	101	100
106	106	105	105	104	104	103	103	102	102	101
107	107	106	106	105	105	104	104	103	103	102
108	108	107	107	106	106	105	105	104	104	104
109	109	108	108	107	107	106	106	106	105	105
110	110	109	109	108	108	108	107	107	106	106
111	111	110	110	109	109	109	108	108	107	107
112	112	111	111	110	110	110	109	109	108	108
113	113	112	112	112	111	111	110	110	110	109
114	114	113	113	113	112	112	111	111	111	110
115	115	114	114	114	113	113	112	112	112	111
116	116	115	115	115	114	114	114	113	113	112
117	117	116	116	116	115	115	115	114	114	114
118	118	117	117	117	116	116	116	115	115	115
119	119	118	118	118	117	117	117	116	116	116
120	120	119	119	119	119	118	118	118	117	117

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

26 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.7

DD	PERCENT of + 3/4 MATERIAL									
	1	2	3	4	5	6	7	8	9	10
121	121	120	120	120	120	119	119	119	118	118
122	122	121	121	121	121	120	120	120	119	119
123	123	122	122	122	122	121	121	121	121	120
124	124	124	123	123	123	122	122	122	122	121
125	125	125	124	124	124	124	123	123	123	122
126	126	126	125	125	125	125	124	124	124	124
127	127	127	126	126	126	126	125	125	125	125
128	128	128	127	127	127	127	126	126	126	126
129	129	129	128	128	128	128	128	127	127	127
130	130	130	129	129	129	129	129	128	128	128
131	131	131	130	130	130	130	130	129	129	129
132	132	132	131	131	131	131	131	131	130	130
133	133	133	133	132	132	132	132	132	131	131
134	134	134	134	133	133	133	133	133	133	132
135	135	135	135	134	134	134	134	134	134	134
136	136	136	136	135	135	135	135	135	135	135
137	137	137	137	137	136	136	136	136	136	136
138	138	138	138	138	137	137	137	137	137	137
139	139	139	139	139	139	138	138	138	138	138
140	140	140	140	140	140	139	139	139	139	139
141	141	141	141	141	141	141	140	140	140	140
142	142	142	142	142	142	142	142	141	141	141
143	143	143	143	143	143	143	143	143	142	142
144	144	144	144	144	144	144	144	144	144	144
145	145	145	145	145	145	145	145	145	145	145
146	146	146	146	146	146	146	146	146	146	146
147	147	147	147	147	147	147	147	147	147	147
148	148	148	148	148	148	148	148	148	148	148
149	149	149	149	149	149	149	149	149	149	149
150	150	150	150	150	150	150	150	150	150	150
151	151	151	151	151	151	151	151	151	151	151
152	152	152	152	152	152	152	152	152	152	152
153	153	153	153	153	153	153	153	153	153	154
154	154	154	154	154	154	154	154	154	155	155
155	155	155	155	155	155	155	156	156	156	156
156	156	156	156	156	156	156	157	157	157	157
157	157	157	157	157	157	158	158	158	158	158
158	158	158	158	158	159	159	159	159	159	159
159	159	159	159	159	160	160	160	160	160	160
160	160	160	160	160	161	161	161	161	161	161

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

27 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.7

DD	PERCENT of + 3/4 MATERIAL									
	11	12	13	14	15	16	17	18	19	20
80	72	71	70	69	68	67	66	65	64	63
81	73	72	71	70	69	68	67	66	65	64
82	74	73	72	71	70	69	68	67	66	65
83	75	74	73	72	71	71	70	69	68	67
84	76	75	74	74	73	72	71	70	69	68
85	77	76	76	75	74	73	72	71	70	69
86	78	78	77	76	75	74	73	72	71	70
87	79	79	78	77	76	75	74	74	73	72
88	81	80	79	78	77	77	76	75	74	73
89	82	81	80	79	79	78	77	76	75	74
90	83	82	81	81	80	79	78	77	76	75
91	84	83	82	82	81	80	79	78	78	77
92	85	84	84	83	82	81	80	80	79	78
93	86	85	85	84	83	82	82	81	80	79
94	87	87	86	85	84	84	83	82	81	80
95	88	88	87	86	86	85	84	83	83	82
96	90	89	88	87	87	86	85	85	84	83
97	91	90	89	89	88	87	87	86	85	84
98	92	91	90	90	89	88	88	87	86	85
99	93	92	92	91	90	90	89	88	87	87
100	94	93	93	92	91	91	90	89	89	88
101	95	95	94	93	93	92	91	91	90	89
102	96	96	95	94	94	93	93	92	91	90
103	97	97	96	96	95	94	94	93	92	92
104	99	98	97	97	96	96	95	94	94	93
105	100	99	99	98	97	97	96	96	95	94
106	101	100	100	99	99	98	97	97	96	95
107	102	101	101	100	100	99	99	98	97	97
108	103	103	102	101	101	100	100	99	99	98
109	104	104	103	103	102	102	101	100	100	99
110	105	105	104	104	103	103	102	102	101	100
111	106	106	105	105	104	104	103	103	102	102
112	108	107	107	106	106	105	105	104	103	103
113	109	108	108	107	107	106	106	105	105	104
114	110	109	109	108	108	107	107	106	106	105
115	111	110	110	110	109	109	108	108	107	107
116	112	112	111	111	110	110	109	109	108	108
117	113	113	112	112	111	111	111	110	110	109
118	114	114	113	113	113	112	112	111	111	110
119	115	115	115	114	114	113	113	113	112	112
120	117	116	116	115	115	115	114	114	113	113

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

28 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.7

DD	PERCENT of + 3/4 MATERIAL									
	11	12	13	14	15	16	17	18	19	20
121	118	117	117	117	116	116	115	115	115	114
122	119	118	118	118	117	117	117	116	116	115
123	120	120	119	119	119	118	118	117	117	117
124	121	121	120	120	120	119	119	119	118	118
125	122	122	122	121	121	121	120	120	120	119
126	123	123	123	122	122	122	121	121	121	120
127	124	124	124	124	123	123	123	122	122	122
128	125	125	125	125	124	124	124	124	123	123
129	127	126	126	126	126	125	125	125	124	124
130	128	128	127	127	127	127	126	126	126	125
131	129	129	128	128	128	128	127	127	127	127
132	130	130	130	129	129	129	129	128	128	128
133	131	131	131	131	130	130	130	130	129	129
134	132	132	132	132	131	131	131	131	131	130
135	133	133	133	133	133	132	132	132	132	132
136	134	134	134	134	134	134	133	133	133	133
137	136	135	135	135	135	135	135	135	134	134
138	137	137	136	136	136	136	136	136	136	135
139	138	138	138	137	137	137	137	137	137	137
140	139	139	139	139	139	138	138	138	138	138
141	140	140	140	140	140	140	140	139	139	139
142	141	141	141	141	141	141	141	141	141	140
143	142	142	142	142	142	142	142	142	142	142
144	143	143	143	143	143	143	143	143	143	143
145	145	145	145	144	144	144	144	144	144	144
146	146	146	146	146	146	146	146	146	145	145
147	147	147	147	147	147	147	147	147	147	147
148	148	148	148	148	148	148	148	148	148	148
149	149	149	149	149	149	149	149	149	149	149
150	150	150	150	150	150	150	150	150	150	150
151	151	151	151	151	151	152	152	152	152	152
152	152	153	153	153	153	153	153	153	153	153
153	154	154	154	154	154	154	154	154	154	154
154	155	155	155	155	155	155	155	155	155	155
155	156	156	156	156	156	156	156	156	157	157
156	157	157	157	157	157	157	158	158	158	158
157	158	158	158	158	159	159	159	159	159	159
158	159	159	159	160	160	160	160	160	160	160
159	160	160	161	161	161	161	161	161	162	162
160	161	162	162	162	162	162	162	163	163	163

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

29 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.7

DD	PERCENT of + 3/4 MATERIAL									
	21	22	23	24	25	26	27	28	29	30
80	62	61	60	58	57	56	55	53	52	51
81	63	62	61	60	59	57	56	55	54	52
82	64	63	62	61	60	59	57	56	55	54
83	66	65	64	62	61	60	59	58	56	55
84	67	66	65	64	63	61	60	59	58	56
85	68	67	66	65	64	63	62	60	59	58
86	69	68	67	66	65	64	63	62	61	59
87	71	70	69	68	67	65	64	63	62	61
88	72	71	70	69	68	67	66	65	63	62
89	73	72	71	70	69	68	67	66	65	64
90	75	74	73	72	71	70	68	67	66	65
91	76	75	74	73	72	71	70	69	68	66
92	77	76	75	74	73	72	71	70	69	68
93	78	77	76	76	75	74	73	72	70	69
94	80	79	78	77	76	75	74	73	72	71
95	81	80	79	78	77	76	75	74	73	72
96	82	81	80	79	79	78	77	76	75	74
97	83	83	82	81	80	79	78	77	76	75
98	85	84	83	82	81	80	79	78	77	76
99	86	85	84	83	83	82	81	80	79	78
100	87	86	86	85	84	83	82	81	80	79
101	88	88	87	86	85	84	84	83	82	81
102	90	89	88	87	87	86	85	84	83	82
103	91	90	89	89	88	87	86	85	85	84
104	92	92	91	90	89	88	88	87	86	85
105	93	93	92	91	91	90	89	88	87	86
106	95	94	93	93	92	91	90	90	89	88
107	96	95	95	94	93	93	92	91	90	89
108	97	97	96	95	95	94	93	92	92	91
109	99	98	97	97	96	95	94	94	93	92
110	100	99	99	98	97	97	96	95	94	94
111	101	100	100	99	99	98	97	97	96	95
112	102	102	101	101	100	99	99	98	97	96
113	104	103	102	102	101	101	100	99	99	98
114	105	104	104	103	103	102	101	101	100	99
115	106	106	105	104	104	103	103	102	101	101
116	107	107	106	106	105	105	104	103	103	102
117	109	108	108	107	107	106	105	105	104	104
118	110	109	109	108	108	107	107	106	106	105
119	111	111	110	110	109	109	108	108	107	106
120	112	112	112	111	111	110	110	109	108	108

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

30 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.7

DD	PERCENT of + 3/4 MATERIAL									
	21	22	23	24	25	26	27	28	29	30
121	114	113	113	112	112	111	111	110	110	109
122	115	115	114	114	113	113	112	112	111	111
123	116	116	115	115	115	114	114	113	113	112
124	118	117	117	116	116	115	115	115	114	114
125	119	118	118	118	117	117	116	116	115	115
126	120	120	119	119	119	118	118	117	117	116
127	121	121	121	120	120	120	119	119	118	118
128	123	122	122	122	121	121	121	120	120	119
129	124	124	123	123	123	122	122	122	121	121
130	125	125	125	124	124	124	123	123	123	122
131	126	126	126	126	125	125	125	124	124	124
132	128	127	127	127	127	126	126	126	125	125
133	129	129	128	128	128	128	127	127	127	126
134	130	130	130	129	129	129	129	128	128	128
135	131	131	131	131	131	130	130	130	130	129
136	133	133	132	132	132	132	131	131	131	131
137	134	134	134	133	133	133	133	133	132	132
138	135	135	135	135	135	134	134	134	134	134
139	137	136	136	136	136	136	136	135	135	135
140	138	138	138	137	137	137	137	137	137	136
141	139	139	139	139	139	138	138	138	138	138
142	140	140	140	140	140	140	140	140	139	139
143	142	142	141	141	141	141	141	141	141	141
144	143	143	143	143	143	143	142	142	142	142
145	144	144	144	144	144	144	144	144	144	144
146	145	145	145	145	145	145	145	145	145	145
147	147	147	147	147	147	147	147	147	146	146
148	148	148	148	148	148	148	148	148	148	148
149	149	149	149	149	149	149	149	149	149	149
150	150	150	151	151	151	151	151	151	151	151
151	152	152	152	152	152	152	152	152	152	152
152	153	153	153	153	153	153	153	153	154	154
153	154	154	154	154	155	155	155	155	155	155
154	156	156	156	156	156	156	156	156	156	156
155	157	157	157	157	157	157	157	158	158	158
156	158	158	158	158	159	159	159	159	159	159
157	159	159	160	160	160	160	160	160	161	161
158	161	161	161	161	161	161	162	162	162	162
159	162	162	162	162	163	163	163	163	163	164
160	163	163	164	164	164	164	164	165	165	165

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

31 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.7

DD	PERCENT of + 3/4 MATERIAL									
	31	32	33	34	35	36	37	38	39	40
80	49	48	46	45	43	42	40	38	36	34
81	51	49	48	46	45	43	41	40	38	36
82	52	51	49	48	46	45	43	41	40	38
83	54	52	51	49	48	46	45	43	41	39
84	55	54	52	51	49	48	46	45	43	41
85	57	55	54	52	51	49	48	46	45	43
86	58	57	55	54	52	51	49	48	46	44
87	59	58	57	55	54	53	51	49	48	46
88	61	60	58	57	56	54	53	51	49	48
89	62	61	60	58	57	56	54	53	51	49
90	64	63	61	60	59	57	56	54	53	51
91	65	64	63	62	60	59	57	56	54	53
92	67	66	64	63	62	60	59	58	56	54
93	68	67	66	65	63	62	61	59	58	56
94	70	68	67	66	65	63	62	61	59	58
95	71	70	69	68	66	65	64	62	61	59
96	73	71	70	69	68	67	65	64	63	61
97	74	73	72	71	69	68	67	66	64	63
98	75	74	73	72	71	70	68	67	66	64
99	77	76	75	74	72	71	70	69	68	66
100	78	77	76	75	74	73	72	70	69	68
101	80	79	78	77	76	74	73	72	71	69
102	81	80	79	78	77	76	75	74	72	71
103	83	82	81	80	79	78	76	75	74	73
104	84	83	82	81	80	79	78	77	76	74
105	86	85	84	83	82	81	80	78	77	76
106	87	86	85	84	83	82	81	80	79	78
107	88	88	87	86	85	84	83	82	81	79
108	90	89	88	87	86	85	84	83	82	81
109	91	91	90	89	88	87	86	85	84	83
110	93	92	91	90	89	88	88	87	86	84
111	94	93	93	92	91	90	89	88	87	86
112	96	95	94	93	92	92	91	90	89	88
113	97	96	96	95	94	93	92	91	90	89
114	99	98	97	96	96	95	94	93	92	91
115	100	99	99	98	97	96	95	95	94	93
116	102	101	100	99	99	98	97	96	95	94
117	103	102	102	101	100	99	99	98	97	96
118	104	104	103	102	102	101	100	99	99	98
119	106	105	105	104	103	103	102	101	100	99
120	107	107	106	105	105	104	103	103	102	101

**WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING**

32 OF 32

DENSITY OF -3/4 INCH MATERIAL WITH THE +3/4 INCH MATERIAL SPECIFIC GRAVITY OF

2.7

DD	PERCENT of + 3/4 MATERIAL									
	31	32	33	34	35	36	37	38	39	40
121	109	108	108	107	106	106	105	104	104	103
122	110	110	109	108	108	107	107	106	105	104
123	112	111	111	110	109	109	108	108	107	106
124	113	113	112	112	111	110	110	109	108	108
125	115	114	114	113	112	112	111	111	110	109
126	116	116	115	115	114	113	113	112	112	111
127	117	117	117	116	116	115	115	114	113	113
128	119	118	118	118	117	117	116	116	115	114
129	120	120	120	119	119	118	118	117	117	116
130	122	121	121	121	120	120	119	119	118	118
131	123	123	122	122	122	121	121	120	120	119
132	125	124	124	124	123	123	122	122	122	121
133	126	126	125	125	125	124	124	124	123	123
134	128	127	127	127	126	126	126	125	125	124
135	129	129	128	128	128	128	127	127	127	126
136	130	130	130	130	129	129	129	128	128	128
137	132	132	131	131	131	131	130	130	130	129
138	133	133	133	133	132	132	132	132	131	131
139	135	135	134	134	134	134	134	133	133	133
140	136	136	136	136	136	135	135	135	135	134
141	138	138	137	137	137	137	137	137	136	136
142	139	139	139	139	139	138	138	138	138	138
143	141	141	140	140	140	140	140	140	140	139
144	142	142	142	142	142	142	141	141	141	141
145	144	143	143	143	143	143	143	143	143	143
146	145	145	145	145	145	145	145	145	145	144
147	146	146	146	146	146	146	146	146	146	146
148	148	148	148	148	148	148	148	148	148	148
149	149	149	149	149	149	149	149	149	149	149
150	151	151	151	151	151	151	151	151	151	151
151	152	152	152	152	152	153	153	153	153	153
152	154	154	154	154	154	154	154	154	154	154
153	155	155	155	155	156	156	156	156	156	156
154	157	157	157	157	157	157	157	158	158	158
155	158	158	158	158	159	159	159	159	159	159
156	159	160	160	160	160	160	161	161	161	161
157	161	161	161	162	162	162	162	162	163	163
158	162	163	163	163	163	164	164	164	164	164
159	164	164	164	165	165	165	165	166	166	166
160	165	166	166	166	166	167	167	167	168	168

WEST VIRGINIA DIVISION OF HIGHWAYS
MATERIALS CONTROL, SOILS AND TESTING DIVISION



LAB NUMBER _____
AUTHORIZATION NUMBER _____
PROJECT NUMBER _____
DISTRICT _____
LOT NUMBER _____
ITEM NUMBER _____

FORM T-316
MP 207.07.20
REV. 08-22

GAUGE NUMBER		TEST NUMBER		1	2	3	4	5
MANUFACTURER'S STANDARDS		DATE						
DENSITY		STATION NUMBER	ft.					
MOISTURE		OFFSET	ft.					
GAUGE STANDARD COUNTS		DEPTH BELOW GRADE	ft.					
DENSITY		LIFT THICKNESS	ft.					
MOISTURE		DEPTH OF SOURCE	ft.					
DB FROM TABLES		Field Density Moisture	TOTAL DRY DENSITY	lb/ft ³				
			MA	MOISTURE	lb/ft ³			
			DB	DRY DENSITY -3/4	lb/ft ³			
			MB	MOISTURE	%			
MA(100) MB = $\frac{MA}{DB}$		PLUS 3/4 MATERIAL DETERMINATION	CA	EXC. MATERIAL + PAN	grams			
CC = CA - CB			CB	PAN	grams			
CF = CD - CE			CC	EXCAVATED MAT.	grams			
CG = $\frac{CF(100)}{CC}$			CD	PLUS +3/4 MAT. + PAN	grams			
PC = PA - PB			CE	PAN	grams			
PD = PC (0.066)			CF	PLUS 3/4 MAT	grams			
PE = $\frac{PD(100)}{100 + MB}$			CG	PLUS 3/4 MAT	%			
PE = $\frac{PD(100)}{100 + SG}$ (RERUN)			CH	SPECIFIC GRAVITY				
RERUN PROCTOR		ONE POINT PROCTOR	RERUN	RERUN	RERUN	RERUN	RERUN	
			PA	WEIGHT SOIL & MOLD	grams			
			PB	MOLD	grams			
			PC	WEIGHT OF SOIL	grams			
			PD	WET DENSITY	lb/ft ³			
SC = SA - SB		STOVE DRIED MOISTURE	PE	DRY DENSITY	lb/ft ³			
SE = SD - SB			SA	WET WEIGHT + PAN	grams			
SF = SC - SE			SB	PAN	grams			
SG = $\frac{SF(100)}{SE}$			SC	WET WEIGHT	grams			
DE = $\frac{DB(100)}{DC}$			SD	DRY WEIGHT + PAN	grams			
DE = $\frac{\sum DE}{5}$			SE	DRY WEIGHT	grams			
QL = $\frac{\bar{X} - T}{R}$			SF	MOISTURE	grams			
		SG	MOISTURE	%				
QL = $\frac{\bar{X} - T}{R}$		MOIST. EVAL	OA	OPTIMUM MOISTURE	%			
			OB	PLUS / MINUS TOLER.				
			OC	PASS / FAIL				
		DEN EVAL	DC	MAXIMUM DENSITY	lb/ft ³			
			DE	RELATIVE DENSITY	%			
			\bar{X}	AVERAGE DE	%	INSPECTORS NAME:		
		T	TARGET	%	INSPECTORS SIGNATURE:			
		QL	QUALITY INDEX					
		DF	WITHIN TOLERANCE	%	PROJECT'S EVALUATION			
		DG	MIN. FOR 100% PAY	%	CHECKED BY:			
		DH	PASS / FAIL		DATE:			